

Start Spot IP65 3-CCT  
Start Spot 610lm 3CCT IP65 WH  
0005565



Product features

- Integrated LED recessed spotlight, fixed, non dimmable, 3 CCT 2700K-3000K-4000K, 100° degree beam angle, polycarbonate white body, low profile 47mm recessed depth, IP65 from the front, IK03, loop-in/loop-out terminals for fast wiring, 87mm bezel diameter, 68-74mm cutout, frosted lens. Additional silver or black bezel can be ordered as accessory.









PRODUCT OVERVIEW

|                                 |                                             |
|---------------------------------|---------------------------------------------|
| Product name                    | Start Spot 610lm 3CCT IP65 WH               |
| Technology                      | LED                                         |
| Cap/Base                        | N/A                                         |
| Housing                         | PC Polycarbonate                            |
| Mount                           | Ceiling recessed mounting                   |
| General application             | Hospitality, Residential & Consumer, Retail |
| ETIM Class                      | EC001744                                    |
| Warranty                        | 3 years                                     |
| Fixture luminous flux (lm)      | 610                                         |
| Luminous flux (lm)              | 610                                         |
| Luminaire efficacy (lm/W)       | 104                                         |
| Colour temperature (K)          | 3000                                        |
| Light colour                    | Neutral White                               |
| CRI (Ra)                        | 80                                          |
| Colour Variation Initial (SDCM) | SDCM6                                       |
| Beam Angle (°)                  | 100                                         |
| Photobiological Risk Group      | RG0                                         |
| Total power consumption (W)     | 6                                           |
| Electrical protection           | Class II                                    |
| Control gear type               | LED driver constant current                 |
| Dimmable                        | No                                          |
| Dimming method                  | N/A                                         |
| LED Flickering Rate             | Low (6% - 20%)                              |
| Housing colour                  | RAL 9003 - Signal white                     |
| IP rating                       | IP65/20                                     |
| IK rating                       | IK03                                        |
| Product EAN number              | 5410288055657                               |

PHOTOMETRY

Start Spot IP65 3-CCT  
Start Spot 610lm 3CCT IP65 WH  
0005565



TECHNICAL DRAWINGS

