


Colossal 600 OPAL  
COLOSSAL 600mm 940 OPAL DIR WHITE DALI EM  
2071188



Product features

- 600mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with polycarbonate opal diffuser. Direct light distribution, 4535lm luminous flux, 41W system power, 111lm/W luminaire efficacy. DALI dimmable. 3 hours integrated emergency. Colour rendering index Ra >90, 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40, IK03. 450mA drive current. Electrical protection Class1, 220-240V. Reported lifetime 66k hours L90B10.



PRODUCT OVERVIEW

|                                 |                                           |
|---------------------------------|-------------------------------------------|
| Product name                    | COLOSSAL 600mm 940 OPAL DIR WHITE DALI EM |
| Technology                      | LED (3 SDCM)                              |
| Cap/Base                        | N/A                                       |
| Housing                         | Aluminium                                 |
| Mount                           | Ceiling surface mounting, Suspended       |
| General application             | Hospitality, Office                       |
| ETIM Class                      | EC002892                                  |
| Warranty                        | 5 years                                   |
| Fixture luminous flux (lm)      | 4535                                      |
| Luminous flux (lm)              | 4535                                      |
| Luminaire efficacy (lm/W)       | 111                                       |
| Colour temperature (K)          | 4000                                      |
| Colour Code                     | 940                                       |
| Light colour                    | Neutral White                             |
| CRI (Ra)                        | 90                                        |
| Colour Variation Initial (SDCM) | SDCM3                                     |
| Glare control                   | < 22                                      |
| Photobiological Risk Group      | RG0                                       |
| Total power consumption (W)     | 41                                        |
| Electrical protection           | Class I                                   |
| Control gear type               | Other                                     |
| Dimmable                        | Yes                                       |
| Dimming method                  | DALI-2                                    |
| LED Flickering Rate             | Ultra low (5% or less)                    |
| Housing colour                  | RAL 9016 - Traffic white / Bezel          |
| IP rating                       | IP40/20                                   |
| IK rating                       | IK07                                      |
| Product EAN number              | 5025768711888                             |

DATA TABLE

## Colossal 600 OPAL

*COLOSSAL 600mm 940 OPAL DIR WHITE DALI EM*

2071188

### General data

|                                  |                                           |
|----------------------------------|-------------------------------------------|
| Product name                     | COLOSSAL 600mm 940 OPAL DIR WHITE DALI EM |
| Technology                       | LED (3 SDCM)                              |
| Cap/Base                         | N/A                                       |
| Housing                          | Aluminium                                 |
| Mount                            | Ceiling surface mounting, Suspended       |
| General application              | Hospitality, Office                       |
| Operating temperature range (°C) | 10°C...+25°C                              |
| ETIM Class                       | EC002892                                  |
| Warranty                         | 5 years                                   |

### Optical data

|                                 |               |
|---------------------------------|---------------|
| Fixture luminous flux (lm)      | 4535          |
| Luminous flux (lm)              | 4535          |
| Luminaire efficacy (lm/W)       | 111           |
| Colour temperature (K)          | 4000          |
| Colour Code                     | 940           |
| Light colour                    | Neutral White |
| CRI (Ra)                        | 90            |
| Colour Variation Initial (SDCM) | SDCM3         |
| Distribution type               | Symmetric     |
| Glare control                   | < 22          |
| Photobiological Risk Group      | RG0           |
| Emergency duration (h)          | 3             |

### Electrical data

|                                                                |                        |
|----------------------------------------------------------------|------------------------|
| Total power consumption (W)                                    | 41                     |
| Mains voltage (V)                                              | 220-240V               |
| Lamp power factor                                              | 0.99                   |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x % | 4.7                    |
| Electrical protection                                          | Class I                |
| Control gear required                                          | No                     |
| Control gear type                                              | Other                  |
| Transformer required                                           | No                     |
| Dimmable                                                       | Yes                    |
| Dimming method                                                 | DALI-2                 |
| Drive current (mA)                                             | 450                    |
| Inrush Current (A)                                             | 23                     |
| Inrush Duration (µs)                                           | 174                    |
| Glow Wire Test (°C)                                            | 650                    |
| Energy Efficiency Class (A->G) of contained light source       | C                      |
| Nominal Frequency (Hz)                                         | 50/60Hz                |
| LED Flickering Rate                                            | Ultra low (5% or less) |
| Max. Luminaires per 10A C Breaker                              | 21                     |
| Max. Luminaires per 13A C Breaker                              | 28                     |
| Max. Luminaires per 16A C Breaker                              | 35                     |
| Max. Luminaires per 20A C Breaker                              | 45                     |
| Max. Luminaires per 10A B Breaker                              | 13                     |

## Colossal 600 OPAL

COLOSSAL 600mm 940 OPAL DIR WHITE DALI EM  
2071188

|                                   |    |
|-----------------------------------|----|
| Max. Luminaires per 13A B Breaker | 17 |
| Max. Luminaires per 16A B Breaker | 21 |
| Max. Luminaires per 20A B Breaker | 27 |

### Lifetime data

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 170000 |
| Lifespan L80 B20 | 145000 |
| Lifespan L90 B10 | 66000  |

### Physical data

|                               |                                  |
|-------------------------------|----------------------------------|
| Housing colour                | RAL 9016 - Traffic white / Bezel |
| IP rating                     | IP40/20                          |
| IK rating                     | IK07                             |
| Diffuser finish               | Opal                             |
| Diffuser material             | PC Polycarbonate                 |
| Nominal Product Height (mm)   | 93                               |
| Nominal Product Diameter (mm) | 604                              |
| Weight (kg)                   | 9.3                              |


### Packaging

|                                       |                |
|---------------------------------------|----------------|
| Single packaging type                 | Carton         |
| Product EAN number                    | 5025768711888  |
| Packaging single length / height (cm) | 14.0           |
| Packaging single width (cm)           | 68.0           |
| Packaging single depth (cm)           | 68.0           |
| DUN14 (outer)                         | 05025768711888 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 14.0           |
| Packaging outer width (cm)            | 68.0           |
| Packaging outer depth (cm)            | 68.0           |

### Safety data

|                                  |       |
|----------------------------------|-------|
| Optimal operating condition (°C) | 10-25 |
|----------------------------------|-------|

## PHOTOMETRY



|     |      |                |       |             |
|-----|------|----------------|-------|-------------|
| 0.5 | 1.42 | E(0°)<br>E(C0) | 54.8° | 8591<br>631 |
| 1.0 | 2.84 | E(0°)<br>E(C0) | 54.8° | 1545<br>158 |
| 1.5 | 4.25 | E(0°)<br>E(C0) | 54.8° | 732<br>70   |
| 2.0 | 5.67 | E(0°)<br>E(C0) | 54.8° | 412<br>39   |
| 2.5 | 7.09 | E(0°)<br>E(C0) | 54.8° | 254<br>25   |
| 3.0 | 8.51 | E(0°)<br>E(C0) | 54.8° | 183<br>18   |

Distance [m]  
Cone diameter [m]  
C0 - C180 (Half beam angle: 106.6°)  
Illuminance [lx]

## Colossal 600 OPAL

*COLOSSAL 600mm 940 OPAL DIR WHITE DALI EM*

2071188

### TECHNICAL DRAWINGS

---

