


START Flex Low Output
START Flex IP20 827 2600lm
0068129



Product features

- 5 metre IP20 LED reel with pre-attached 3M adhesive type; equipped with 300 LEDs ,24V; 2700K; CRI80; SDCM 3



PRODUCT OVERVIEW

Product name	START Flex IP20 827 2600lm
Technology	LED
Mount	Other
General application	Hospitality, Retail
ETIM Class	EC002706
E-number FI	4276593
Warranty	5 years
Fixture luminous flux (lm)	2600
Luminaire efficacy (lm/W)	108
Colour temperature (K)	2700
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Beam Angle (°)	N/A
Photobiological Risk Group	RG1
Light source included	INTEGRATED LED
Total power consumption (W)	24
Electrical protection	Class III
Dimmable	Yes
Dimming method	Other
IP rating	IP20
IK rating	IK00
Product EAN number	5410288681290

DATA TABLE

General data	
Product name	START Flex IP20 827 2600lm
Technology	LED
Mount	Other
General application	Hospitality, Retail
Operating temperature range (°C)	-20°C...+40°C

START Flex Low Output

START Flex IP20 827 2600lm
0068129

Performance ambient temperature Tq (°C)	25
ETIM Class	EC002706
E-number FI	4276593
Warranty	5 years

Optical data

Fixture luminous flux (lm)	2600
Luminaire efficacy (lm/W)	108
Colour temperature (K)	2700
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Beam Angle (°)	N/A
Photobiological Risk Group	RG1
Emergency duration (h)	3

Electrical data

Light source included	INTEGRATED LED
Total power consumption (W)	24
Mains voltage (V)	24V
Electrical protection	Class III
Control gear required	Yes
Transformer required	No
Dimmable	Yes
Dimming method	Other
Drive current (mA)	1000
Glow Wire Test (°C)	650
Lamp Energy Label (class)	F

Lifetime data

Lifespan L70 B50	54000
Lifespan L70 B10	54000
Lifespan L80 B10	50000
Lifespan L90 B10	44000

Physical data

IP rating	IP20
IK rating	IK00
Nominal Product Length (mm)	5000
Nominal Product Width (mm)	8
Nominal Product Height (mm)	1.2
Weight (kg)	0.1

Packaging

Single packaging type	Carton
Product EAN number	5410288681290
Packaging single length / height (cm)	23.5
Packaging single width (cm)	22.5


START Flex Low Output
START Flex IP20 827 2600lm
0068129

Packaging single depth (cm)	3.0
DUN14 (outer)	15410288681297
Units per outer package	20
Packaging outer length / height (cm)	49.0
Packaging outer width (cm)	35.0
Packaging outer depth (cm)	24.0


Safety data

Optimal operating condition (°C)	-20-40
----------------------------------	--------

PHOTOMETRY



TECHNICAL DRAWINGS



START Flex Low Output
START Flex IP20 827 2600lm
0068129



ENERGY
SYLVANIA

0068129



24


kWh/1000h



2019/2015

START Flex Low Output
START Flex IP20 827 2600lm
0068129

**ENERG**
SYLVANIA
0068129



24
kWh/1000h

