


Raiden 40KLM

Raiden IP66 40KLM 840 Asymmetric Wide DALI
2824106



Product features

- Outdoor and indoor floodlight range with in house design, comes complete with 1m flying lead and adjustable bracket, aluminium housing, RAL 9022 - Pearl light grey, clear glass diffuser, IP66, IK08, Class I, 4000K, DALI dimmable, 38900lm, 294W, 132lm/W, CRI80, Asymmetric Wide beam angle 110°50°, 100000 hrs L90B50 lifespan, 561x569x76mm (LxWxH) dimensions, 13.5kg weight. Ball-impact-resistance according to DIN57710-13 VDE 0710 13/5.81, DIN 18032-3 only with the separate wire guard accessory fitted.



PRODUCT OVERVIEW

Product name	Raiden IP66 40KLM 840 Asymmetric Wide DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
General application	Logistics & Industry
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	38900
Luminaire efficacy (lm/W)	132
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	110°50°
Photobiological Risk Group	RG2
Total power consumption (W)	294
Electrical protection	Class I
Dimmable	Yes
Dimming method	DALI-2
Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Product EAN number	5025768241064

DATA TABLE

General data

Product name	Raiden IP66 40KLM 840 Asymmetric Wide DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
General application	Logistics & Industry
Operating temperature range (°C)	-40°C...+50°C

Raiden 40KLM

Raiden IP66 40KLM 840 Asymmetric Wide DALI
2824106

Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Warranty	5 years

Optical data

Fixture luminous flux (lm)	38900
Luminaire efficacy (lm/W)	132
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	110°50
Photobiological Risk Group	RG2

Electrical data

Total power consumption (W)	294
Mains voltage (V)	220-240V
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	20
Electrical protection	Class I
Control gear required	No
Transformer required	No
Dimmable	Yes
Dimming method	DALI-2
Drive current (mA)	6000
Inrush Current (A)	110
Inrush Duration (µs)	500
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	2
Max. Luminaires per 13A C Breaker	2
Max. Luminaires per 16A C Breaker	4
Max. Luminaires per 20A C Breaker	4
Max. Luminaires per 13A B Breaker	1
Max. Luminaires per 16A B Breaker	2
Max. Luminaires per 20A B Breaker	3
Mains surge immunity (differential mode - > L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	10

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	89000
Lifespan L90 B50	100000

Raiden 40KLM

Raiden IP66 40KLM 840 Asymmetric Wide DALI
2824106

Physical data

Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Nominal Product Length (mm)	561
Nominal Product Width (mm)	569
Nominal Product Height (mm)	76
Weight (kg)	13.5


Packaging

Single packaging type	Carton
Product EAN number	5025768241064
Packaging single length / height (cm)	63.0
Packaging single width (cm)	63.0
Packaging single depth (cm)	14.0
DUN14 (outer)	05025768241064
Units per outer package	1
Packaging outer length / height (cm)	63.0
Packaging outer width (cm)	63.0
Packaging outer depth (cm)	14.0

Safety data

Optimal operating condition (°C)	-40-50
----------------------------------	--------

PHOTOMETRY



TECHNICAL DRAWINGS

