

Colossal 600 Prismatic

COLOSSAL 600mm 940 PRISM DIR+HAL WHITE EM

2071228

General data

Product name	COLOSSAL 600mm 940 PRISM DIR+HAL WHITE EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
General application	Hospitality, Office
Operating temperature range (°C)	10°C...+25°C
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	3485
Luminous flux (lm)	3485
Luminaire efficacy (lm/W)	109
Colour temperature (K)	4000
Colour Code	940
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0
Emergency duration (h)	3

Electrical data

Total power consumption (W)	32.1
Mains voltage (V)	220-240V
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	20
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Transformer required	No
Dimmable	No
Dimming method	N/A
Drive current (mA)	350
Inrush Current (A)	22
Inrush Duration (µs)	250
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	28
Max. Luminaires per 13A C Breaker	36
Max. Luminaires per 16A C Breaker	45
Max. Luminaires per 20A C Breaker	56
Max. Luminaires per 10A B Breaker	17

Colossal 600 Prismatic

COLOSSAL 600mm 940 PRISM DIR+HAL WHITE EM
2071228

Max. Luminaires per 13A B Breaker	22
Max. Luminaires per 16A B Breaker	27
Max. Luminaires per 20A B Breaker	34

Lifetime data

Lifespan L70 B50	170000
Lifespan L80 B20	145000
Lifespan L90 B10	66000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK07
Diffuser finish	Prismatic
Diffuser material	PMMA Acrylic
Nominal Product Height (mm)	93
Nominal Product Diameter (mm)	604
Weight (kg)	9.3


Packaging

Single packaging type	Carton
Product EAN number	5025768712281
Packaging single length / height (cm)	14.0
Packaging single width (cm)	68.0
Packaging single depth (cm)	68.0
DUN14 (outer)	05025768712281
Units per outer package	1
Packaging outer length / height (cm)	14.0
Packaging outer width (cm)	68.0
Packaging outer depth (cm)	68.0

Safety data

Optimal operating condition (°C)	10-25
----------------------------------	-------

PHOTOMETRY



0.5	1.07	E(0°) E(C0)	47.0°	8248 991
1.0	2.14	E(0°) E(C0)	47.0°	1562 248
1.5	3.22	E(0°) E(C0)	47.0°	694 110
2.0	4.29	E(0°) E(C0)	47.0°	390 62
2.5	5.36	E(0°) E(C0)	47.0°	230 40
3.0	6.43	E(0°) E(C0)	47.0°	174 28

Distance [m] Cone diameter [m] Illuminance [lx]

C0 - C180 (Half beam angle: 94.0°)

Colossal 600 Prismatic

COLOSSAL 600mm 940 PRISM DIR+HAL WHITE EM

2071228

TECHNICAL DRAWINGS

