

Start Flood Flat without PIR
Start Flood Flat IP65 2000LM 840 Black
0050110



Product features

- The streamlined, durable, lightweight die-cast aluminium body makes Start Flood Flat a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black (RAL9017) housing, white reflector, 2000 lm, 18 W, 111 lm/W, 4000K, non dimmable, CRI>80, IP65, IK06, Class I, lifespan L70:B50: 90000 hrs, 110 x 123 x 26 mm (L x W x H). Weight: 0.39kg.




PRODUCT OVERVIEW

Product name	Start Flood Flat IP65 2000LM 840 Black
Technology	LED
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4579529
Warranty	3 years
Fixture luminous flux (lm)	2000
Luminaire efficacy (lm/W)	111
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	110
Photobiological Risk Group	RG1
Total power consumption (W)	18
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Low (6% - 20%)
Housing colour	Black
IP rating	IP65
IK rating	IK06
Product EAN number	5410288501109

PHOTOMETRY

Start Flood Flat without PIR
Start Flood Flat IP65 2000LM 840 Black
0050110



TECHNICAL DRAWINGS

