


INSAVER SLIM 175
Insaver Slim UGR19 175 IP44 1600lm 840
0030303



Product features

- Insaver Slim is a ceiling recessed LED downlight (IP44 from the front). Die-cast aluminium body, loop in loop out connector for quick installation, Non dimmable LED driver, 13W; 1600lm; 123lm/W; 4000K; UGR <19 with shallow product depth 60mm. Meets TP(a) requirements.




PRODUCT OVERVIEW

Product name	Insaver Slim UGR19 175 IP44 1600lm 840
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Office, Retail
ETIM Class	EC001744
E-number FI	4276917
Warranty	5 years
Fixture luminous flux (lm)	1600
Luminaire efficacy (lm/W)	123
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	60
Beam Angle (°)	NA
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	13
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288303031

PHOTOMETRY

INSAVER SLIM 175
Insaver Slim UGR19 175 IP44 1600lm 840
0030303



TECHNICAL DRAWINGS

