

SylSafe Spot
SylSafe XSpot OA R EM3 NM MS
0041775



Product features


- SylSafe XSpot OA R EM3 NM MS is a miniature emergency recessed spotlight with small form factor - cut-out diameter: 10mm. Non-maintained 3 hr emergency duration with NiMH rechargeable battery. Recharge period 24 hours. Quick and easy installation with driver module and battery pack contained in articulated case that can placed near the luminaire. Suitable for sheet metal installation. 80lm, 2.8W, IK03, IP20. Power Factor 0.45. Class II electrical construction.



PRODUCT OVERVIEW

Product name	SylSafe XSpot OA R EM3 NM MS
Technology	LED
Type	LED
Mount	Ceiling recessed mounting
General application	Office, Hospitality, Retail, Education, Museums & Galleries
ETIM Class	EC001957
Warranty	5 years
Fixture luminous flux (lm)	80
Luminaire efficacy (lm/W)	29
Colour temperature (K)	5700
CRI (Ra)	70
Photobiological Risk Group	RG2
Luminous flux (emergency) (lm)	80
Light source included	INTEGRATED LED
Electrical protection	Class II
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288417752

PHOTOMETRY



SylSafe Spot

SylSafe XSpot OA R EM3 NM MS

0041775

TECHNICAL DRAWINGS

