

Pixo Medium

Pixo Medium 3000lm 940 NB MB WB BLK

0005449



Product features

- Integrated LED spotlight, Textured Black - RAL9005, simple and slick integral design with no driver box and without any visible screws, ideal for retail applications, die-cast aluminium body, passive cooling heatsink. Beam angle: 36°, additional lenses 24° and 54° beam angle included, color temperature: 4000k, total system power: 32W, total fixture output: 3024 lm, LOR: 100%, colour rendering: Ra: 90 typical, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, electronic driver, non-dimmable, ultra low LED flickering rate (5% or less), power factor: >0.90, electrical protection: Class I, Global Track 3 Circuit GA69 adapter suitable for Global trac 3-circuit tracks, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 345°, vertical tilt: 90°, dimensions: Ø81x86x283, weight: 0.892kg.









PRODUCT OVERVIEW

Product name	Pixo Medium 3000lm 940 NB MB WB BLK
Technology	LED
Environment	Indoor
General application	Museums & Galleries, Residential & Consumer, Retail
ETIM Class	EC001744
E-number FI	4278249
Warranty	5 years
Fixture luminous flux (lm)	3024
Luminaire efficacy (lm/W)	95
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	36
Photobiological Risk Group	RG1
Total power consumption (W)	32
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
IP rating	IP20
IK rating	IK03
Product EAN number	5410288054490

PHOTOMETRY

Pixo Medium
Pixo Medium 3000lm 940 NB MB WB BLK
0005449



TECHNICAL DRAWINGS

