

START DOWNLIGHT IP44 205

START Downlight 205 IP44 DALI 2000Lm 840 0030337

Product features



Ceiling recessed LED downlight IP44 (from the front), with only 60mm product depth and 205mm cutout. Supplied with DALI Tridonic push dim driver with loop in - out option (28000671). Ideal replacement for 1x42W CFL downlights. The polycarbonate diffuser allows for a wider light distribution and increased spacings between luminiares. Die-cast aluminium body, 2000LM, 20W, 100lm/W, 4000K, Driver Current: 600mA, CRI80, 74° beam angle, IP44 from the front, IK07, (HxW) 60x205mm, Class 2, 220-240V. Meets TP(a) requirements.


























PRODUCT OVERVIEW


Product name	START Downlight 205 IP44 DALI 2000Lm 840
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Logistics & Industry, Office
ETIM Class	EC001744
E-number FI	4278165
Warranty	5 years
Fixture luminous flux (lm)	2000
Luminous flux (lm)	2000
Luminaire efficacy (lm/W)	100
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	80
Glare control	< 26
Photobiological Risk Group	RG0
Total power consumption (W)	20
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288303376



START DOWNLIGHT IP44 205 START Downlight 205 IP44 DALI 2000Lm 840 0030337

PHOTOMETRY





TECHNICAL DRAWINGS

