

ToLEDo Retro Candle Dimmable

ToLEDo RT Candle V5 ST DIM 470LM 840 E14 SL 0029368



Product features

- Perfect for decorative and general lighting applications and creates a warm ambience similar to traditional lamps
- The versatile ToLEDo Retro Candle range is the ideal replacement for halogen and incandescent lamps and perfect for chandeliers and decorative applications
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- Gives same sparkling light effect as the incandescent lamp
- Dimensionally identical to incandescent lamps fits all fixtures
- Environment-friendly no mercury and lower CO2 emissions
- Dimmable with approved dimmers











PRODUCT OVERVIEW

Product name ToLEDo RT Candle V5 ST DIM 470LM 840 E14 SL Technology Watt (Rated) (W) 4.5 Type LED exchangeable Cap/Base E14 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4740925 Warranty 3 years Luminous flux (Im) Colour temperature (K) Light colour CRI (Ra) Colour Variation Initial (SDCM) Photobiological Risk Group Wattage (W) Product Voltage (V) Dimmable Average life (Nominal) (h) 15000		
Watt (Rated) (W) Type LED exchangeable Cap/Base E14 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4740925 Warranty 3 years Luminous flux (Im) Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) Photobiological Risk Group Wattage (W) Product Voltage (V) Dimmable LED exchangeable Consumer E14 4.5 4.5 4.5 4.5 4.5 4.5 4.5 4.5 4.5 4.	Product name	ToLEDo RT Candle V5 ST DIM 470LM 840 E14 SL
Type LED exchangeable Cap/Base E14 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4740925 Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.5 Product Voltage (V) 230 Dimmable Yes	Technology	LED
Cap/Base E14 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4740925 Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.5 Product Voltage (V) 230 Dimmable Yes	Watt (Rated) (W)	4.5
Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4740925 Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.5 Product Voltage (V) 230 Dimmable	Туре	LED exchangeable
General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4740925 Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.5 Product Voltage (V) 230 Dimmable Yes	Cap/Base	E14
ETIM Class EC001959 E-number FI 4740925 Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.5 Product Voltage (V) 230 Dimmable Yes	Fixture rating	Open
E-number FI 4740925 Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.5 Product Voltage (V) 230 Dimmable Yes	General application	Hospitality, Residential & Consumer
Warranty 3 years Luminous flux (Im) 470 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.5 Product Voltage (V) 230 Dimmable Yes	ETIM Class	EC001959
Luminous flux (Im) 470 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.5 Product Voltage (V) 230 Dimmable Yes	E-number FI	4740925
Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.5 Product Voltage (V) 230 Dimmable Yes	Warranty	3 years
Light colour CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group Wattage (W) 4.5 Product Voltage (V) Dimmable Cool White 80 SDCM6 PAG1 V-5 Product Voltage (V) 230 Ves	Luminous flux (Im)	470
CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 4.5 Product Voltage (V) 230 Dimmable Yes	Colour temperature (K)	4000
Colour Variation Initial (SDCM) Photobiological Risk Group Wattage (W) Product Voltage (V) Dimmable SDCM6 RG1 4.5 Product Voltage (V) Yes	Light colour	Cool White
Photobiological Risk Group RG1 Wattage (W) 4.5 Product Voltage (V) 230 Dimmable Yes	CRI (Ra)	80
Wattage (W) 4.5 Product Voltage (V) 230 Dimmable Yes	Colour Variation Initial (SDCM)	SDCM6
Product Voltage (V) 230 Dimmable Yes	Photobiological Risk Group	RG1
Dimmable Yes	Wattage (W)	4.5
	Product Voltage (V)	230
Average life (Nominal) (h) 15000	Dimmable	Yes
	Average life (Nominal) (h)	15000




ToLEDo Retro Candle Dimmable ToLEDo RT Candle V5 ST DIM 470LM 840 E14 SL 0029368

Product EAN number

5410288293684

PHOTOMETRY



TECHNICAL DRAWINGS

