

Kalani Asymmetric
Kalani IP66 20KLM 840 ASYM
0048539



Product features

- Exterior LED Floodlight, comes complete with 1500mm flying lead and adjustable bracket, aluminium housing, clear glass diffuser, IP66, IK08, Class I, 4000K, Non-dimming, 20100lm, 150W, 134lm/W, CRI80, Asymmetrical Wide beam angle (65° x 120° imax@55°), 100000 hrs L80B20 lifespan, 451 x 330 x 77mm (LxWxD) dimensions, 4.6kg weight.




PRODUCT OVERVIEW

Product name	Kalani IP66 20KLM 840 ASYM
Technology	LED
General application	Logistics & Industry
ETIM Class	EC001744
E-number FI	4579570
Warranty	5 years
Fixture luminous flux (lm)	20100
Luminaire efficacy (lm/W)	134
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	65*120
Photobiological Risk Group	RG1
Total power consumption (W)	150
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
IP rating	IP66
IK rating	IK08
Product EAN number	5410288485393

PHOTOMETRY

Kalani Asymmetric *Kalani IP66 20KLM 840 ASYM* 0048539



TECHNICAL DRAWINGS

