


START Flex High Output  
START Flex IP20 840 11750lm  
0068115



Product features

- 5 metre IP20 LED reel with pre-attached 3M adhesive type; equipped with 420 LEDs; 11750lm per 5m (2350lm per 1m); 24V; 4000K; CRI80; SDCM 3. Needs to be used with aluminium profile for cooling LED chips purpose and therefore assuring longer lifetime (Profile HO Surface 16 0022604 can be used);Compatible with emergency packs: 0046600, 0046601






PRODUCT OVERVIEW

|                                 |                             |
|---------------------------------|-----------------------------|
| Product name                    | START Flex IP20 840 11750lm |
| Technology                      | LED                         |
| Mount                           | Other                       |
| General application             | Hospitality, Retail         |
| ETIM Class                      | EC002706                    |
| E-number FI                     | 4276901                     |
| Warranty                        | 5 years                     |
| Fixture luminous flux (lm)      | 11750                       |
| Luminaire efficacy (lm/W)       | 142                         |
| Colour temperature (K)          | 4000                        |
| CRI (Ra)                        | 80                          |
| Colour Variation Initial (SDCM) | SDCM3                       |
| Beam Angle (°)                  | 120                         |
| Beam Angle (°)                  | N/A                         |
| Photobiological Risk Group      | RG1                         |
| Total power consumption (W)     | 82.5                        |
| Electrical protection           | Class III                   |
| Dimmable                        | Yes                         |
| Dimming method                  | Other                       |
| IP rating                       | IP20                        |
| IK rating                       | IK00                        |
| Product EAN number              | 5410288681153               |

PHOTOMETRY

START Flex High Output  
START Flex IP20 840 11750lm  
0068115



TECHNICAL DRAWINGS

