

Start eco Surface Wall Adjustable Up & Down IP54

START eco Surface Wall Adjustable Up & Down IP54 2x150lm 830 BLK
0047910



Product features

- Exterior adjustable surface wall up and down light luminaire, black aluminium - RAL9005, 290lm, 5W, 58lm/W, 3000K, Driver Current: 700mA, CRI:80+, 220-240V, IP54, IK05, 30.000 hrs (L70), (HxWxD) 108x108x109mm, Class 1, energy class: A++, A+, A




PRODUCT OVERVIEW

Product name	START eco Surface Wall Adjustable Up & Down IP54 2x150lm 830 BLK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Wall surface mounted
Environment	External
General application	Residential & Consumer
ETIM Class	EC002892
E-number FI	4579447
Warranty	3 years
Fixture luminous flux (lm)	2x150
Luminaire efficacy (lm/W)	58
LOR (%)	100
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	94
Photobiological Risk Group	RG1
Total power consumption (W)	5
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL 9005 - Jet black
IP rating	IP54
IK rating	IK05
Product EAN number	5410288479101

PHOTOMETRY

Start eco Surface Wall Adjustable Up & Down IP54 *START eco Surface Wall Adjustable Up & Down IP54 2x150lm 830 BLK* 0047910



Distance [m]	Cone diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	1.22	0.50	1113
	1.13	0.45	142
1.0	2.44	1.00	278
	2.25	0.90	38
1.5	3.67	1.50	151
	3.38	1.35	16
2.0	4.89	2.00	73
	4.51	1.80	9
2.5	6.11	2.50	48
	5.63	2.25	9
3.0	7.33	3.00	31
	6.76	2.70	5

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 90.9°) — C90 - C270 (Half beam angle: 101.4°)

TECHNICAL DRAWINGS

