


INSAVER SLIM 225
Insaver Slim 225 IP44 3050lm 840
0030307



Product features

- Insaver Slim is a ceiling recessed LED downlight (IP44 from the front), Die-cast aluminium body, loop in loop out connector for quick installation, Non dimmable LED driver, 25W; 3050lm; 122lm/W; 4000K; UGR <22 with shallow product depth 65mm. Meets TP(a) requirements.




PRODUCT OVERVIEW

Product name	Insaver Slim 225 IP44 3050lm 840
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Office, Retail
ETIM Class	EC001744
E-number FI	4276921
Warranty	5 years
Fixture luminous flux (lm)	3050
Luminaire efficacy (lm/W)	122
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	60
Beam Angle (°)	NA
Glare control	< 22
Photobiological Risk Group	RG1
Total power consumption (W)	25
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288303079

PHOTOMETRY

INSAVER SLIM 225
Insaver Slim 225 IP44 3050lm 840
0030307



TECHNICAL DRAWINGS

