

Colossal 600 Prismatic


COLOSSAL 600mm 830 PRISM DIR+HAL WHITE DALI EM

2071206



Product features

- 600mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with PMMA prismatic diffuser. Direct/indirect (halo) light distribution, 3900lm luminuous flux, 32.1W system power, 121lm/W luminaire efficacy. DALI dimmable. 3 hours integrated emergency. Colour rendering index Ra >80, 3000K Warm White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40, IK03. 350mA drive current. UGR 19. Electrical protection Class1, 220-240V. Reported lifetime 66k hours L90B10.




PRODUCT OVERVIEW

|                                 |                                                |
|---------------------------------|------------------------------------------------|
| Product name                    | COLOSSAL 600mm 830 PRISM DIR+HAL WHITE DALI EM |
| Technology                      | LED (3 SDCM)                                   |
| Cap/Base                        | N/A                                            |
| Housing                         | Aluminium                                      |
| Mount                           | Suspended                                      |
| General application             | Hospitality, Office                            |
| ETIM Class                      | EC002892                                       |
| Warranty                        | 5 years                                        |
| Fixture luminous flux (lm)      | 3900                                           |
| Luminous flux (lm)              | 3900                                           |
| Luminaire efficacy (lm/W)       | 121                                            |
| Colour temperature (K)          | 3000                                           |
| Colour Code                     | 830                                            |
| Light colour                    | Warm White                                     |
| CRI (Ra)                        | 80                                             |
| Colour Variation Initial (SDCM) | SDCM3                                          |
| Glare control                   | < 19                                           |
| Photobiological Risk Group      | RG0                                            |
| Total power consumption (W)     | 32.2                                           |
| Electrical protection           | Class I                                        |
| Control gear type               | Other                                          |
| Dimmable                        | Yes                                            |
| Dimming method                  | DALI-2                                         |
| LED Flickering Rate             | Ultra low (5% or less)                         |
| Housing colour                  | RAL 9016 - Traffic white / Bezel               |
| IP rating                       | IP40/20                                        |
| IK rating                       | IK07                                           |
| Product EAN number              | 5025768712069                                  |

PHOTOMETRY

Colossal 600 Prismatic  
COLOSSAL 600mm 830 PRISM DIR+HAL WHITE DALI EM  
2071206



TECHNICAL DRAWINGS

