

# Giotto LED 335 GIOTTO 335 4000K RECESSED MW SENSOR 3034806



#### **Product features**

Ambient and decorative round, recessed mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 2350lm, 18.2W, 129lm/W, 4000K, CRI 80, non-dimmable, integral microwave sensor. 100,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.
























#### PRODUCT OVERVIEW


Technology Cap/Base N/A Housing PC Polycarbonate Mount Ceiling recessed mounting Environment Indoor General application ETIM Class EC002892 Warranty Fixture luminous flux (Im) 2225 Luminous flux (Im) 2225 Luminaire efficacy (Im/W) Colour temperature (K) 4000 Colour Code 840 Light colour CRI (Ra) 80 Colour Variation Initial (SDCM) Beam Angle (*) Glare control Photoblological Risk Group Total power consumption (W) 23 Electrical protection Control gear mounting Dimmable Dimmable Dimmable Dimming method N/A LED Flickering Rate House IN 1971348061 Product EAN number R711971348061	Product name	GIOTTO 335 4000K RECESSED MW SENSOR
HousingPC PolycarbonateMountCeiling recessed mountingEnvironmentIndoorGeneral applicationHospitality, Logistics & IndustryETIM ClassEC002892Warranty5 yearsFixture luminous flux (Im)2225Luminous flux (Im)2225Luminaire efficacy (Im/W)97Colour temperature (K)4000Colour Code840Light colourNeutral WhiteCRI (Ra)80Colour Variation Initial (SDCM)SDCM3Beam Angle (°)120Glare control< 26	Technology	LED
Mount       Ceiling recessed mounting         Environment       Indoor         General application       Hospitality, Logistics & Industry         ETIM Class       EC002892         Warranty       5 years         Fixture luminous flux (Im)       2225         Luminous flux (Im)       97         Colour temperature (K)       4000         Colour Code       840         Light colour       Neutral White         CRI (Ra)       80         Colour Variation Initial (SDCM)       SDCM3         Beam Angle (°)       120         Glare control       < 26         Photobiological Risk Group       RG0         Total power consumption (W)       23         Electrical protection       Class I         Control gear type       LED driver constant current         Control gear mounting       Integrated         Dimmable       No         Dimmap method       N/A         LED Flickering Rate       Ultra low (5% or less)         Housing colour       White         IP rating       IP44         IK rating       IK10	Cap/Base	N/A
Environment Indoor General application Hospitality, Logistics & Industry ETIM Class EC002892 Warranty 5 years Fixture luminous flux (Im) 2225 Luminous flux (Im) 2225 Luminaire efficacy (Im/W) 97 Colour temperature (K) 4000 Colour Code 840 Light colour Neutral White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3 Beam Angle (°) 120 Glare control < 26 Photobiological Risk Group RG0 Total power consumption (W) 23 Electrical protection Class I Control gear type LED driver constant current Control gear mounting Integrated Dimmable No Dimming method N/A LED Flickering Rate Ultra low (5% or less) Hussing colour White IP rating IP44 IK rating IK10	Housing	PC Polycarbonate
General application Hospitality, Logistics & Industry  ETIM Class EC002892  Warranty 5 years  Fixture luminous flux (Im) 2225  Luminous flux (Im) 2225  Luminaire efficacy (Im/W) 97  Colour temperature (K) 4000  Colour Code 840  Light colour Neutral White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 26  Photobiological Risk Group RG0  Total power consumption (W) 23  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No  Dimming method N/A  LED Flickering Rate Ultra low (5% or less)  Housing colour White  IP rating IP44  IK rating IK10	Mount	Ceiling recessed mounting
ETIM Class EC002892  Warranty 5 years  Fixture luminous flux (Im) 2225  Luminous flux (Im) 2225  Luminaire efficacy (Im/W) 97  Colour temperature (K) 4000  Colour Code 840  Light colour Neutral White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 26  Photobiological Risk Group RG0  Total power consumption (W) 23  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No  Dimming method N/A  LED Flickering Rate Ultra low (5% or less)  Housing colour White  IP rating IP44  IK rating IK10	Environment	Indoor
Warranty 5 years  Fixture luminous flux (Im) 2225  Luminous flux (Im) 2225  Luminaire efficacy (Im/W) 97  Colour temperature (K) 4000  Colour Code 840  Light colour Neutral White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 26  Photobiological Risk Group RG0  Total power consumption (W) 23  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No  Dimming method N/A  LED Flickering Rate Ultra low (5% or less)  Housing colour White  IP rating IP44  IK rating IK10	General application	Hospitality, Logistics & Industry
Fixture luminous flux (Im) 2225  Luminous flux (Im) 2225  Luminaire efficacy (Im/W) 97  Colour temperature (K) 4000  Colour Code 840  Light colour Neutral White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 26  Photobiological Risk Group RG0  Total power consumption (W) 23  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No  Dimming method N/A  LED Flickering Rate Ultra low (5% or less)  Housing colour White  IP rating IP44  IK rating IK10	ETIM Class	EC002892
Luminous flux (Im)  Luminaire efficacy (Im/W)  Colour temperature (K)  4000  Colour Code  840  Light colour  Neutral White  CRI (Ra)  80  Colour Variation Initial (SDCM)  Beam Angle (°)  120  Glare control  Photobiological Risk Group  Total power consumption (W)  23  Electrical protection  Control gear type  LED driver constant current  Control gear mounting  Integrated  Dimmable  No  Dimming method  N/A  LED Flickering Rate  Ultra low (5% or less)  Housing colour  White  IP rating  IR44  IK rating  IK 10	Warranty	5 years
Luminaire efficacy (Im/W) 97  Colour temperature (K) 4000  Colour Code 840  Light colour Neutral White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 26  Photobiological Risk Group RG0  Total power consumption (W) 23  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No  Dimming method N/A  LED Flickering Rate Ultra low (5% or less)  Housing colour White  IP rating IP44  IK rating IK10	Fixture luminous flux (lm)	2225
Colour temperature (K) 4000  Colour Code 840  Light colour Neutral White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 26  Photobiological Risk Group RG0  Total power consumption (W) 23  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No  Dimming method N/A  LED Flickering Rate Ultra low (5% or less)  Housing colour White  IP rating IP44  IK rating IK10	Luminous flux (lm)	2225
Colour Code 840  Light colour Neutral White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 26  Photobiological Risk Group RG0  Total power consumption (W) 23  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No  Dimming method N/A  LED Flickering Rate Ultra low (5% or less)  Housing colour White  IP rating IP44  IK rating IK10	Luminaire efficacy (lm/W)	97
Light colour CRI (Ra) 80 Colour Variation Initial (SDCM) Beam Angle (°) 120 Glare control < 26 Photobiological Risk Group RG0 Total power consumption (W) 23 Electrical protection Class I Control gear type LED driver constant current Control gear mounting Integrated Dimmable No Dimming method N/A LED Flickering Rate Ultra low (5% or less) Housing colour White IP rating IK 10	Colour temperature (K)	4000
CRI (Ra) Colour Variation Initial (SDCM) Beam Angle (°) 120 Glare control < 26 Photobiological Risk Group Total power consumption (W) 23 Electrical protection Control gear type LED driver constant current Control gear mounting Integrated Dimmable No Dimming method N/A LED Flickering Rate Ultra low (5% or less) Housing colour White IP rating IK 10	Colour Code	840
Colour Variation Initial (SDCM)  Beam Angle (°)  Glare control  Colour Variation Initial (SDCM)  Beam Angle (°)  Glare control  Colour Variation Initial (SDCM)  RG0  Total power consumption (W)  Electrical protection  Class I  Control gear type  LED driver constant current  Control gear mounting  Integrated  Dimmable  No  Dimming method  N/A  LED Flickering Rate  Ultra low (5% or less)  Housing colour  White  IP rating  IP44  IK rating  IK 10	Light colour	Neutral White
Beam Angle (°)  Glare control  < 26  Photobiological Risk Group  Total power consumption (W)  Electrical protection  Control gear type  Control gear mounting  Dimmable  Dimmable  No  Dimming method  LED Flickering Rate  Ultra low (5% or less)  Housing colour  IP rating  IK 10	CRI (Ra)	80
Glare control < 26 Photobiological Risk Group RG0 Total power consumption (W) 23 Electrical protection Class I Control gear type LED driver constant current Control gear mounting Integrated Dimmable No Dimming method N/A LED Flickering Rate Ultra low (5% or less) Housing colour White IP rating IP44 IK rating IK10	Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group  Total power consumption (W)  Electrical protection  Control gear type  LED driver constant current  Control gear mounting  Integrated  Dimmable  No  Dimming method  LED Flickering Rate  Ultra low (5% or less)  Housing colour  White  IP rating  IK 10	Beam Angle (°)	120
Total power consumption (W)  Electrical protection  Control gear type  LED driver constant current  Control gear mounting  Dimmable  No  Dimming method  LED Flickering Rate  Ultra low (5% or less)  Housing colour  IP rating  IK 10	Glare control	< 26
Electrical protection Control gear type LED driver constant current Control gear mounting Integrated Dimmable No Dimming method N/A LED Flickering Rate Ultra low (5% or less) Housing colour White IP rating IK rating IK 10	Photobiological Risk Group	RG0
Control gear type  Control gear mounting  Integrated  Dimmable  No  Dimming method  LED Flickering Rate  Ultra low (5% or less)  Housing colour  IP rating  IK 10	Total power consumption (W)	23
Control gear mounting Dimmable No Dimming method N/A LED Flickering Rate Ultra low (5% or less) Housing colour White IP rating IP44 IK rating IK10	Electrical protection	Class I
Dimmable No Dimming method N/A  LED Flickering Rate Ultra low (5% or less)  Housing colour White  IP rating IP44  IK rating IK10	Control gear type	LED driver constant current
Dimming method N/A  LED Flickering Rate Ultra low (5% or less)  Housing colour White  IP rating IP44  IK rating IK10	Control gear mounting	Integrated
LED Flickering Rate  Ultra low (5% or less)  Housing colour  White  IP rating  IP44  IK rating  IK10	Dimmable	No
Housing colour White IP rating IP44 IK rating IK10	Dimming method	N/A
IP rating IP44 IK rating IK10	LED Flickering Rate	Ultra low (5% or less)
IK rating IK10	Housing colour	White
	IP rating	IP44
Product EAN number 8711971348061	IK rating	
	Product EAN number	8711971348061



# Giotto LED 335 GIOTTO 335 4000K RECESSED MW SENSOR 3034806

## **PHOTOMETRY**





### **TECHNICAL DRAWINGS**

