

RouteLED 2
ROUTELED II OPEN AREA DALI
2059461



Product features

- Miniature self-test (DALI) emergency recessed luminaire downlight with open area optic, non-maintained 3 hr emergency, standalone unit with inverter module and rechargeable battery (NiMH), quick and easy installation with inverter module and battery pack contained in articulated case that can pass through 40mm cutout, 219lm, 3W, IK07, beam angle 148 degrees, 230V, 50-60Hz, recharge period 24 hours, Power Factor 0.45, charge current 300mA, LxWxD (mm) 416x29x26.



PRODUCT OVERVIEW



Product name	ROUTELED II OPEN AREA DALI
Technology	LED
Type	Integrated LED
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Office, Hospitality, Retail, Education
ETIM Class	EC001957
Warranty	5 years
Fixture luminous flux (lm)	219
LOR (%)	100
Colour temperature (K)	5000
Light colour	Cool White
CRI (Ra)	70
Colour Variation Initial (SDCM)	SDCM5
Colour Consistency (SDCM)	5
Beam Angle (°)	145
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	219
Luminous flux (emergency) (lm)	219
Product Voltage (V)	230
Electrical protection	Class II
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768594610

PHOTOMETRY

RouteLED 2

ROUTELED II OPEN AREA DALI

2059461



TECHNICAL DRAWINGS

