

START Waterproof Tubular IP66
START Waterproof Tubular 1200 IP66 5000lm 840 PC
0047180



Product features



- **START Waterproof Tubular** is an aesthetically attractive integrated LED fixture. Easy to install with 304 stainless steel fixing brackets for ceiling mounting. Polycarbonate housing; 4000K; 35W; 5000lm; High efficiency with 143lm/W and lumen maintenance L80:B50 of 54,000 hours lifetime. IP66; IK10; Class I; 1195mm x 70mm. Can be suspended with additional accessory (SKU 0046035).



PRODUCT OVERVIEW

Product name	START Waterproof Tubular 1200 IP66 5000lm 840 PC
Technology	LED
General application	Logistics & Industry
ETIM Class	EC000109
E-number FI	4309098
Warranty	5 years
Fixture luminous flux (lm)	5000
Luminaire efficacy (lm/W)	143
Colour temperature (K)	4000
CRI (Ra)	80
Beam Angle (°)	120
Photobiological Risk Group	RG1
Total power consumption (W)	35
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
IP rating	IP66
IK rating	IK10
Product EAN number	5410288471808

PHOTOMETRY



START Waterproof Tubular IP66

START Waterproof Tubular 1200 IP66 5000lm 840 PC

0047180

TECHNICAL DRAWINGS

