

# Giotto LED 305 GIOTTO 305 3000K SURFACE EMERGENCY 3034785



#### **Product features**

 Ambient and decorative round, surface mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 1625lm, 16W, 102lm/W, 3000K, CRI 80, non-dimmable, integral 3 hour maintained emergency, 100,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.

















Product name Technology LED Cap/Base N/A Housing PC Polycarbonate Mount Ceiling recessed mounting, Wall surface mounted Environment Indoor General application ETIM Class EC002892 Warranty Fixture luminous flux (Im) Luminous flux (Im) Luminaire efficacy (Im/W) Colour temperature (K) Solour Code Light colour CRI (Ra) Colour Variation Initial (SDCM) Beam Angle (°) Glare control Photobiological Risk Group Luminous flux (emergency) (Im) Total power consumption (W) ED description Control gear type LED driver constant current Control gear mounting Dimmable Dimma
Cap/Base N/A Housing PC Polycarbonate Mount Ceiling recessed mounting, Wall surface mounted Environment Indoor General application Hospitality, Logistics & Industry ETIM Class EC002892 Warranty 5 years Fixture luminous flux (Im) 1490 Luminous flux (Im) 1490 Luminaire efficacy (Im/W) 75 Colour temperature (K) 3000 Colour Code 830 Light colour Warm White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3 Beam Angle (*) 120 Glare control < 24 Photobiological Risk Group RG0 Luminous flux (emergency) (Im) 102 Total power consumption (W) 20 Electrical protection Class I Control gear type LED driver constant current Control gear mounting Integrated Dimmable No
Housing PC Polycarbonate  Mount Ceiling recessed mounting, Wall surface mounted Environment Indoor  General application Hospitality, Logistics & Industry  ETIM Class EC002892  Warranty 5 years  Fixture luminous flux (Im) 1490  Luminous flux (Im) 1490  Luminaire efficacy (Im/W) 75  Colour temperature (K) 3000  Colour Code 830  Light colour Warm White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 24  Photobiological Risk Group RG0  Luminous flux (emergency) (Im) 102  Total power consumption (W) 20  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No
MountCeiling recessed mounting, Wall surface mountedEnvironmentIndoorGeneral applicationHospitality, Logistics & IndustryETIM ClassEC002892Warranty5 yearsFixture luminous flux (Im)1490Luminous flux (Im)1490Luminaire efficacy (Im/W)75Colour temperature (K)3000Colour Code830Light colourWarm WhiteCRI (Ra)80Colour Variation Initial (SDCM)SDCM3Beam Angle (°)120Glare control< 24Photobiological Risk GroupRG0Luminous flux (emergency) (Im)102Total power consumption (W)20Electrical protectionClass IControl gear typeLED driver constant currentControl gear mountingIntegratedDimmableNo
Environment Indoor  General application Hospitality, Logistics & Industry  ETIM Class EC002892  Warranty 5 years  Fixture luminous flux (Im) 1490  Luminous flux (Im) 1490  Luminaire efficacy (Im/W) 75  Colour temperature (K) 3000  Colour Code 830  Light colour Warm White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 24  Photobiological Risk Group RG0  Luminous flux (emergency) (Im) 102  Total power consumption (W) 20  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No
Environment Indoor  General application Hospitality, Logistics & Industry  ETIM Class EC002892  Warranty 5 years  Fixture luminous flux (Im) 1490  Luminous flux (Im) 1490  Luminaire efficacy (Im/W) 75  Colour temperature (K) 3000  Colour Code 830  Light colour Warm White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 24  Photobiological Risk Group RG0  Luminous flux (emergency) (Im) 102  Total power consumption (W) 20  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No
ETIM Class EC002892  Warranty 5 years  Fixture luminous flux (Im) 1490  Luminous flux (Im) 1490  Luminaire efficacy (Im/W) 75  Colour temperature (K) 3000  Colour Code 830  Light colour  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 24  Photobiological Risk Group RG0  Luminous flux (emergency) (Im) 102  Total power consumption (W) 20  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No
Warranty 5 years  Fixture luminous flux (Im) 1490  Luminous flux (Im) 1490  Luminaire efficacy (Im/W) 75  Colour temperature (K) 3000  Colour Code 830  Light colour Warm White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 24  Photobiological Risk Group RG0  Luminous flux (emergency) (Im) 102  Total power consumption (W) 20  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No
Fixture luminous flux (Im)  Luminous flux (Im)  Luminaire efficacy (Im/W)  Colour temperature (K)  Solour Code  Signature (Im)  Warm White  CRI (Ra)  Colour Variation Initial (SDCM)  Beam Angle (°)  Glare control  Photobiological Risk Group  Luminous flux (emergency) (Im)  Total power consumption (W)  Electrical protection  Control gear type  Control gear mounting  Integrated  Dimmable  Luminous flux (Im)  1490  Luminous Riux (Im)  1490  Lago  Rago  Luminous Riux (Im)  120  Class I  Control gear mounting  Integrated  Dimmable  No
Luminous flux (Im)1490Luminaire efficacy (Im/W)75Colour temperature (K)3000Colour Code830Light colourWarm WhiteCRI (Ra)80Colour Variation Initial (SDCM)SDCM3Beam Angle (°)120Glare control< 24Photobiological Risk GroupRG0Luminous flux (emergency) (Im)102Total power consumption (W)20Electrical protectionClass IControl gear typeLED driver constant currentControl gear mountingIntegratedDimmableNo
Luminaire efficacy (Im/W) 75  Colour temperature (K) 3000  Colour Code 830  Light colour Warm White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 24  Photobiological Risk Group RG0  Luminous flux (emergency) (Im) 102  Total power consumption (W) 20  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No
Colour temperature (K) 3000  Colour Code 830  Light colour Warm White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 24  Photobiological Risk Group RG0  Luminous flux (emergency) (Im) 102  Total power consumption (W) 20  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No
Colour Code 830  Light colour Warm White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 24  Photobiological Risk Group RG0  Luminous flux (emergency) (Im) 102  Total power consumption (W) 20  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No
Light colour  CRI (Ra)  80  Colour Variation Initial (SDCM)  Beam Angle (°)  120  Glare control  Photobiological Risk Group  Luminous flux (emergency) (Im)  Total power consumption (W)  Electrical protection  Control gear type  Control gear mounting  Dimmable  Warm White  80  80  CDCM3  BDCM3  BDCM3  BDCM3  BDCM3  BDCM3  L20  C94  Photobiological Risk Group  RG0  Luminous flux (emergency) (Im)  102  Total power consumption (W)  20  Electrical protection  Class I  Control gear type  LED driver constant current  No
CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM3  Beam Angle (°) 120  Glare control < 24  Photobiological Risk Group RG0  Luminous flux (emergency) (Im) 102  Total power consumption (W) 20  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No
Colour Variation Initial (SDCM)  Beam Angle (°)  Glare control  Photobiological Risk Group  Luminous flux (emergency) (Im)  Total power consumption (W)  Electrical protection  Control gear type  LED driver constant current  Control gear mounting  Dimmable  SDCM3  SDCM3  BDCM3  BDCM3  E40  C24  Photobiological Risk Group  RG0  Luminous flux (emergency) (Im)  102  Columnous flux (emergency) (Im)  Columnous flux (emergency) (Im)  102  Electrical protection  Class I  Control gear type  LED driver constant current  No
Beam Angle (°) 120 Glare control < 24 Photobiological Risk Group RG0 Luminous flux (emergency) (Im) 102 Total power consumption (W) 20 Electrical protection Class I Control gear type LED driver constant current Control gear mounting Integrated Dimmable No
Glare control < 24 Photobiological Risk Group RG0 Luminous flux (emergency) (Im) 102 Total power consumption (W) 20 Electrical protection Class I Control gear type LED driver constant current Control gear mounting Integrated Dimmable No
Photobiological Risk Group RG0 Luminous flux (emergency) (Im) 102 Total power consumption (W) 20 Electrical protection Class I Control gear type LED driver constant current Control gear mounting Integrated Dimmable No
Luminous flux (emergency) (Im) 102  Total power consumption (W) 20  Electrical protection Class I  Control gear type LED driver constant current  Control gear mounting Integrated  Dimmable No
Total power consumption (W)  Electrical protection  Control gear type  LED driver constant current  Control gear mounting  Integrated  No
Electrical protection Control gear type LED driver constant current Control gear mounting Integrated No
Control gear type  Control gear mounting  Dimmable  LED driver constant current  Integrated  No
Control gear mounting Integrated  Dimmable No
<b>Dimmable</b> No
Dimming method N/A
- managamental
LED Flickering Rate Ultra low (5% or less)
Housing colour White
IP rating IP44
IK rating IK10





# Giotto LED 305 GIOTTO 305 3000K SURFACE EMERGENCY 3034785

**Product EAN number** 

8711971347859

### **PHOTOMETRY**





#### **TECHNICAL DRAWINGS**

