

START Flex Low Output
START Flex IP65 830 2650lm
0068127



Product features

- 5 metre IP65 LED reel with pre-attached 3M adhesive type; equipped with 300 LEDs; 2650lm per 5m (530lm per 1m); 24V; 3000K; CRI80; SDCM 3;Compatible with emergency packs: 0046600, 0046601



PRODUCT OVERVIEW

Product name	START Flex IP65 830 2650lm
Technology	LED
Housing	Other
Mount	Other
General application	Hospitality, Retail
ETIM Class	EC002706
E-number FI	4276597
Warranty	5 years
Fixture luminous flux (lm)	2650
Luminaire efficacy (lm/W)	110
Colour temperature (K)	3000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Beam Angle (°)	N/A
Photobiological Risk Group	RG1
Total power consumption (W)	24
Electrical protection	Class III
Dimmable	Yes
Dimming method	Other
Housing colour	Beige
IP rating	IP65
IK rating	IK00
Product EAN number	5410288681276



PHOTOMETRY

START Flex Low Output
START Flex IP65 830 2650lm
0068127

0.5	1.73 1.34	E07 E180 E270	892 44 19
1.0	3.45 2.67	E07 E180 E270	173 11 5
1.5	5.18 4.01	E07 E180 E270	77 5 2
2.0	6.90 5.35	E07 E180 E270	40 3 1
2.5	8.63 6.68	E07 E180 E270	26 2 1
3.0	10.35 8.02	E07 E180 E270	19 1 1

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 105.4°)
— C90 - C270 (Half beam angle: 119.8°)



TECHNICAL DRAWINGS

