

Giotto LED 235 GIOTTO 235 4000K RECESSED DALI 3034758



Product features

 Ambient and decorative round, recessed mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 1150lm, 10.1W, 114lm/W, 4000K, CRI 80, DALI, 100,000 hours lumen maintenance (L70:B50). Drive current: 275mA, IP44, IK10, Class I, 220-240V.



























| Product name | GIOTTO 235 4000K RECESSED DALI |
|---------------------------------|-----------------------------------|
| Technology | LED |
| Cap/Base | N/A |
| Housing | PC Polycarbonate |
| Mount | Ceiling recessed mounting |
| Environment | Indoor |
| General application | Hospitality, Logistics & Industry |
| ETIM Class | EC002892 |
| E-number FI | 4270060 |
| Warranty | 5 years |
| Fixture luminous flux (lm) | 1098 |
| Luminous flux (Im) | 1098 |
| Luminaire efficacy (lm/W) | 92 |
| Colour temperature (K) | 4000 |
| Colour Code | 840 |
| Light colour | Neutral White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 120 |
| Glare control | < 25 |
| Photobiological Risk Group | RG0 |
| Total power consumption (W) | 12 |
| Electrical protection | Class I |
| Control gear type | LED driver constant current |
| Control gear mounting | Integrated |
| Dimmable | Yes |
| Dimming method | DALI |
| Minimum dimming level (%) | 1 |
| LED Flickering Rate | Ultra low (5% or less) |
| Housing colour | White |
| IP rating | IP44 |
| IK rating | IK10 |
| Product EAN number | 8711971347583 |
| | |



Giotto LED 235 GIOTTO 235 4000K RECESSED DALI 3034758

PHOTOMETRY





TECHNICAL DRAWINGS

