

## Giotto LED 335

GIOTTO 335 4000K SURFACE 1-10V MW SENSOR

3034812



### Product features

- Ambient and decorative round, surface mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 2350lm, 18.2W, 129lm/W, 4000K, CRI 80, 1-10V dimmable, integral microwave sensor. 100,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.



### PRODUCT OVERVIEW

Product name	GIOTTO 335 4000K SURFACE 1-10V MW SENSOR
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Environment	Indoor
General application	Hospitality, Logistics & Industry
ETIM Class	EC002892
E-number FI	4270267
Warranty	5 years
Fixture luminous flux (lm)	2225
Luminous flux (lm)	2225
Luminaire efficacy (lm/W)	97
Colour temperature (K)	4000
Colour Code	840
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Glare control	< 26
Photobiological Risk Group	RG0
Total power consumption (W)	23
Electrical protection	Class I
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	Yes
Dimming method	1-10V (Analogue)
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP44
IK rating	IK10
Product EAN number	8711971348122

## Giotto LED 335

### GIOTTO 335 4000K SURFACE 1-10V MW SENSOR


#### 3034812

### PHOTOMETRY

0.5	1.59	E(0°) E(C0)	2724 207
1.0	3.18	E(0°) E(C0)	684 81
1.5	4.76	E(0°) E(C0)	364 23
2.0	6.35	E(0°) E(C0)	171 13
2.5	7.94	E(0°) E(C0)	109 8
3.0	9.53	E(0°) E(C0)	78 6

Distance [m]      Cone diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 115.6°)



### TECHNICAL DRAWINGS

