

RefLED Superia Retro MR16

RefLED Superia Retro MR16 V2 600LM 830 36° SL 0029233



Product features

Compact, energy efficient and exceptional value for money productSame shape and size as halogen MR16 lampCompact Cluster SMD technology enabling high efficiency with halogen lookReduced visible heat sink from the frontAvailable in 36 degreeHigh lumen efficacy12V AC/DC25,000 hours average rated life5 years warranty













PRODUCT OVERVIEW

Product name	RefLED Superia Retro MR16 V2 600LM 830 36° SL
Technology	LED
Watt (Rated) (W)	6
Туре	LED exchangeable
Cap/Base	GU5.3
Fixture rating	Open
General application	Education, Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4741113
Warranty	3 years
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Beam Angle (°)	36
Photobiological Risk Group	RG1
Wattage (W)	6
Product Voltage (V)	12
Dimmable	No
Average life (Nominal) (h)	25000
Product EAN number	5410288292335

DATA TABLE

General data	
Product name	RefLED Superia Retro MR16 V2 600LM 830 36° SL
Technology	LED
Watt (Rated) (W)	6
Туре	LED exchangeable
Cap/Base	GU5.3
Fixture rating	Open
General application	Education, Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C+40°C



Performance ambient temperature Tq	25
(°C)	
ETIM Class	EC001959
E-number FI	4741113
Warranty	3 years
Optical data	
	0000
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80 CDCMC
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	
Luminous Intensity (cd) Beam Angle (°)	1000 36
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal	70
life (%)	70
Electrical data	
	6
Wattage (W)	49
Equivalent watt (W)	12
Product Voltage (V) Control gear required	No
No. Of switching cycles before premature	>50000
failures	>50000
Transformer required	Yes
Dimmable	No
Lamp Energy Label (class)	F
Lifetime data	
	25000
Lifespan L70 B50	25000 25000
Average life (Nominal) (h)	
Average life (Rated) (h)	25000
Physical data	
Nominal Product Length (mm)	44
Nominal Product Diameter (mm)	50
Weight (kg)	0.035
(
Packaging	
Single packaging type	Carton
Product EAN number	5410288292335
Packaging single length / height (cm)	8.2
Packaging single width (cm)	6.1
Packaging single depth (cm)	5.1
DUN14 (inner)	25410288292339
Units per inner package	6
Packaging inner length / height (cm)	9.5
Packaging inner width (cm)	17.0
Packaging inner depth (cm)	13.5




DUN14 (outer)	15410288292332
Units per outer package	36
Packaging outer length / height (cm)	20.0
Packaging outer width (cm)	41.5
Packaging outer depth (cm)	18.0
Safety data	
Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes

Not Suitable for totally enclosed fixtures

PHOTOMETRY

Safety message



TECHNICAL DRAWINGS

