

Eco Linear Double Ended R7s
DE 118MM ECO 230V 120W R7S BL
0022578



Product features

- Instant illumination, - Excellent colour rendering, - Sparkling light output, - Transformer free operation, - Average life 1500hours, - Suitable for outdoor floodlighting/security lighting, - Suitable for interior floodlighting, uplighting and wall washing.



PRODUCT OVERVIEW

Product name	DE 118MM ECO 230V 120W R7S BL
Technology	Halogen
Watt (Rated) (W)	120
Lamp shape	Tube, double-ended
Type	Halogen
Cap/Base	R7s
Lamp finish	Clear
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC000038
Warranty	2 years
Luminous flux (lm)	2245
Colour temperature (K)	3000
Light colour	Homelight
CRI (Ra)	100
Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable
Wattage (W)	120
Product Voltage (V)	230
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Average life (Nominal) (h)	1500
Product EAN number	5410288225784

DATA TABLE

General data	
Product name	DE 118MM ECO 230V 120W R7S BL
Technology	Halogen
Watt (Rated) (W)	120

Eco Linear Double Ended R7s

DE 118MM ECO 230V 120W R7S BL
0022578

Lamp shape	Tube, double-ended
Type	Halogen
Cap/Base	R7s
Lamp finish	Clear
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC000038
Warranty	2 years

Optical data

Luminous flux (lm)	2245
Luminous flux (Rated) (lm)	2245
Colour temperature (K)	3000
Light colour	Homelight
CRI (Ra)	100
Colour Variation Initial (SDCM)	N/A
Adjustable chromaticity	N
Photobiological Risk Group	Not applicable

Electrical data

Wattage (W)	120
Equivalent watt (W)	150
Starting time (max) (s)	0.01
Warm-up time to 60% of full light (max) (s)	Instant full light
Mains voltage (V)	230V
Product Voltage (V)	230
Lamp power factor	1
Control gear required	No
No. Of switching cycles before premature failures	>10000
Transformer required	No
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Lamp Energy Label (class)	G
kWh per 1000 hours burning time	120

Lifetime data

Average life (Nominal) (h)	1500
Average life (Rated) (h)	1500

Physical data

Nominal Product Length (mm)	119.6
Nominal Product Diameter (mm)	12
Max. Lamp Length (mm) - C/L	120
Max. Lamp Diameter (mm) - D	12
Weight (kg)	0.005

Eco Linear Double Ended R7s
DE 118MM ECO 230V 120W R7S BL
0022578


Packaging

Single packaging type	Mix blister(20% carton, 80% pl
Product EAN number	5410288225784
Packaging single length / height (cm)	14.0
Packaging single width (cm)	12.0
Packaging single depth (cm)	1.2
DUN14 (outer)	15410288225781
Units per outer package	10
Packaging outer length / height (cm)	14.9
Packaging outer width (cm)	14.5
Packaging outer depth (cm)	12.4

Safety data

Breakage cleaning instructions	N/A
Recommendation for disposal at end of life	Not Applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	None

PHOTOMETRY



TECHNICAL DRAWINGS




Eco Linear Double Ended R7s DE 118MM ECO 230V 120W R7S BL 0022578



SYLVANIA

0022578



120
kWh/1000h




2019/2015

Eco Linear Double Ended R7s
DE 118MM ECO 230V 120W R7S BL
0022578



0022578



120
kWh/1000h



2019/2015