

ToLEDo T8 CCG and AC 25K

ToLEDo T8 V4 4FT 1800LM 840 25K
0029302



Product features

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps
- Omni-directional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes
- Lumen output - 1800lm
- High lumen efficacy - 103 lm/W
- Switching cycles - 100,000X
- Average rated life 25,000 hours
- Lamp length - 1200mm
- Wide beam angle
- Suitable for general illumination in offices, supermarkets, department stores, parking lots
- Suitable for operation with electromagnetic gears/CCG and direct mains operation (220-240V)
- 2-Year warranty



PRODUCT OVERVIEW

Product name	ToLEDo T8 V4 4FT 1800LM 840 25K
Technology	LED
Watt (Rated) (W)	17.5
Lamp shape	Tube, double-ended
Type	LED exchangeable
Cap/Base	G13
Lamp finish	Opal
Fixture rating	Open
General application	Logistics & Industry, Education, Residential & Consumer, Office
ETIM Class	EC001959
E-number FI	4941321
Warranty	2 years
Luminous flux (lm)	1800
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	180
Photobiological Risk Group	RG0
Wattage (W)	17.5
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	25000
IP rating	IP20
Product EAN number	5410288293028

DATA TABLE

General data

Product name	ToLEDo T8 V4 4FT 1800LM 840 25K
--------------	---------------------------------

ToLEDo T8 CCG and AC 25K

ToLEDo T8 V4 4FT 1800LM 840 25K

0029302

Technology	LED
Watt (Rated) (W)	17.5
Lamp shape	Tube, double-ended
Type	LED exchangeable
Cap/Base	G13
Lamp finish	Opal
Fixture rating	Open
General application	Logistics & Industry, Education, Residential & Consumer, Office
Operating temperature range (°C)	-20°C...+45°C
Performance ambient temperature Tq (°C)	55
ETIM Class	EC001959
E-number FI	4941321
Warranty	2 years

Optical data

Luminous flux (lm)	1800
Luminous flux (Rated) (lm)	1800
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	180
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	17.5
Product Voltage (V)	230
Lamp power factor	0.5
Control gear required	No
No. Of switching cycles before premature failures	>50000
Transformer required	No
Dimmable	No
Inrush Current (A)	8.0
Inrush Duration (µs)	420
Lamp Energy Label (class)	F
Max. Luminaires per 16A C Breaker	20
Max. Luminaires per 16A B Breaker	10

Lifetime data

Lifespan L70 B50	25000
Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

Physical data

IP rating	IP20
Nominal Product Length (mm)	1213.6

ToLEDo T8 CCG and AC 25K
ToLEDo T8 V4 4FT 1800LM 840 25K
0029302

Nominal Product Diameter (mm)	28
Weight (kg)	0.25


Packaging

Single packaging type	Carton
Product EAN number	5410288293028
Packaging single length / height (cm)	126.0
Packaging single width (cm)	2.8
Packaging single depth (cm)	2.8
DUN14 (outer)	15410288293025
Units per outer package	10
Packaging outer length / height (cm)	129.0
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	8.5


Safety data

Optimal operating condition (°C)	-20-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS




ToLEDo T8 CCG and AC 25K
ToLEDo T8 V4 4FT 1800LM 840 25K
0029302

**ENERG**

SYLVANIA

0029302




18
kWh/1000h



2019/2015

ToLEDo T8 CCG and AC 25K
ToLEDo T8 V4 4FT 1800LM 840 25K
0029302

 **ENERG** 
SYLVANIA
0029302



18
kWh/1000h



2019/2015