


Start Surface IP66 Ø350mm Sensor Dim
START SURFACE IP66 2400LM 830 MW SENS IK10 WHT
0049020



Product features

- Sensor Dim LED exterior surface mounted luminaire, 350mm diameter, 2400lm as max. lumen output, can be adjusted down to 1650lm by internal switch, 25W max. power consumption, 96lm/W efficacy, 3000K color temperature, CRI80, IP66, IK10, 50,000 hours (L70), white housing, vandal resistant. Integrated Microwave occupancy sensor with daylight harvest, dimming and corridor function, supplied with anti-theft screws




PRODUCT OVERVIEW

Product name	START SURFACE IP66 2400LM 830 MW SENS IK10 WHT
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Environment	Indoor, Outdoor
General application	Hospitality
ETIM Class	EC002892
E-number FI	4579495
Warranty	5 years
Fixture luminous flux (lm)	2400
Luminaire efficacy (lm/W)	96
LOR (%)	100
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Glare control	< 26
Photobiological Risk Group	RG0
Total power consumption (W)	25
Electrical protection	Class II
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	Yes
Dimming method	Other
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP66
IK rating	IK10
Product EAN number	5410288490205

Start Surface IP66 Ø350mm Sensor Dim
START SURFACE IP66 2400LM 830 MW SENS IK10 WHT
0049020

PHOTOMETRY



TECHNICAL DRAWINGS

Start Surface IP66 Ø350mm Sensor Dim

START SURFACE IP66 2400LM 830 MW SENS IK10 WHT

0049020

