Equinox *EQUINOX 165 2500 TRIMLESS 940 SSC* **2059939**

Product features



Equinox is an elegant and innovative luminaire designed using the latest optical technology. It is a high
quality and efficient lighting solution for office, hospitality, and retail environments. It creates
inspirational halo effects regulated by a unique adjustable optic system. It is Sylsmart dimmable
downlight luminaire, Colour rendering index Ra >90, Colour temperature: 4000K Neutral White, Class
II, Cut out dimensions: 165mm. Low Glare UGR<19.
















PRODUCT OVERVIEW

Product name	EQUINOX 165 2500 TRIMLESS 940 SSC
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Office
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	2500
Luminaire efficacy (Im/W)	125
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	64
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	20
Electrical protection	Class II
Control gear type	LED driver constant current
Control gear mounting	Remote
Dimmable	Yes
Dimming method	SylSmart SSC
Minimum dimming level (%)	1
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK02
Product EAN number	5025768599394

Equinox *EQUINOX 165 2500 TRIMLESS 940 SSC* **2059939**

PHOTOMETRY



TECHNICAL DRAWINGS

