

## ToLEDo G9 ToLEDo Retro G9 CL 250LM 840 SL 0029666



#### **Product features**

- LED retrofit replacement for halogen G9 mains voltage capsules
- ToLEDo Retro G9 has the same look and feel as halogen design thanks to glass construction body and wide light distribution
- Compact design
- Omni-directional light distribution
- 250lm = 25W halogen G9 lamp
- 90% energy saving
- Non-dimmable
- Suitable for chandeliers, interior display, shop windows, decorative and general lighting applications












### PRODUCT OVERVIEW

Product name ToLEDo Retro G9 CL 250LM 840 SL Technology LED Watt (Rated) (W) 2.2 Type LED exchangeable Cap/Base G9 Fixture rating Open General application ETIM Class EC001959 E-number FI 4741139 Warranty 3 years Luminous flux (Im) Colour temperature (K) Light colour CRI (Ra) Colour Variation Initial (SDCM) Photobiological Risk Group Wattage (W) Product Voltage (V) Dimmable Average life (Nominal) (h)  15000	Technology Watt (Rated) (W) 2.2 Type LED exchangeable Cap/Base G9 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4741139 Warranty 3 years Luminous flux (Im) 250 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) Photobiological Risk Group Wattage (W) Product Voltage (V) Dimmable Average life (Nominal) (h)  LED  4.2  Product Voltage (Nominal) (Nominal) (Nomes)  LED  4.2  LED  4.2  LED  4.2  ED  6.2	Dec decet wares	T   ED   D   00 01 0501 M 040 01
Watt (Rated) (W)  Type  LED exchangeable  Cap/Base  G9  Fixture rating  Open  General application  ETIM Class  EC001959  E-number FI  4741139  Warranty  3 years  Luminous flux (Im)  Colour temperature (K)  4000  Light colour  CRI (Ra)  Colour Variation Initial (SDCM)  Photobiological Risk Group  Wattage (W)  Product Voltage (V)  Dimmable  LED exchangeable  LED exchangeable  Colour  Colour Nessidential & Consumer  ETIM Class  EC001959  E-001959  E-00195	Watt (Rated) (W)  Type  Cap/Base  G9  Fixture rating  General application  ETIM Class  E-number FI  Warranty  Luminous flux (Im)  Colour temperature (K)  Light colour  CRI (Ra)  Colour Variation Initial (SDCM)  Photobiological Risk Group  Wattage (W)  Average life (Nominal) (h)  LED exchangeable  2.2  LED exchangeable  Cope  LED exchangeable  Cap/Base  G9  Hospitality, Residential & Consumer  EC001959  E-001959		
Type LED exchangeable Cap/Base G9 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4741139 Warranty 3 years Luminous flux (Im) 250 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 230 Dimmable No	Type LED exchangeable Cap/Base G9 Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4741139 Warranty 3 years Luminous flux (Im) 250 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 2.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 15000	Technology	LED
Cap/BaseG9Fixture ratingOpenGeneral applicationHospitality, Residential & ConsumerETIM ClassEC001959E-number FI4741139Warranty3 yearsLuminous flux (Im)250Colour temperature (K)4000Light colourCool WhiteCRI (Ra)80Colour Variation Initial (SDCM)SDCM6Photobiological Risk GroupRG1Wattage (W)2.2Product Voltage (V)230DimmableNo	Cap/Base G9  Fixture rating Open  General application Hospitality, Residential & Consumer  ETIM Class EC001959  E-number FI 4741139  Warranty 3 years  Luminous flux (Im) 250  Colour temperature (K) 4000  Light colour Cool White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM6  Photobiological Risk Group RG1  Wattage (W) 2.2  Product Voltage (V) 230  Dimmable No  Average life (Nominal) (h) 15000	Watt (Rated) (W)	2.2
Fixture rating General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4741139 Warranty 3 years Luminous flux (Im) Colour temperature (K) 4000 Light colour CRI (Ra) Colour Variation Initial (SDCM) Photobiological Risk Group Wattage (W) Product Voltage (V) Dimmable  Open Hospitality, Residential & Consumer EC001959 E-001959 E-0019	Fixture rating Open General application Hospitality, Residential & Consumer ETIM Class EC001959 E-number FI 4741139 Warranty 3 years Luminous flux (Im) 250 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 2.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 15000	Туре	LED exchangeable
General application Hospitality, Residential & Consumer  ETIM Class EC001959  E-number FI 4741139  Warranty 3 years  Luminous flux (Im) 250  Colour temperature (K) 4000  Light colour Cool White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM6  Photobiological Risk Group RG1  Wattage (W) 2.2  Product Voltage (V) 230  Dimmable No	General application Hospitality, Residential & Consumer  ETIM Class EC001959  E-number FI 4741139  Warranty 3 years  Luminous flux (Im) 250  Colour temperature (K) 4000  Light colour Cool White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM6  Photobiological Risk Group RG1  Wattage (W) 2.2  Product Voltage (V) 230  Dimmable No  Average life (Nominal) (h) 15000	Cap/Base	G9
ETIM Class         EC001959           E-number FI         4741139           Warranty         3 years           Luminous flux (Im)         250           Colour temperature (K)         4000           Light colour         Cool White           CRI (Ra)         80           Colour Variation Initial (SDCM)         SDCM6           Photobiological Risk Group         RG1           Wattage (W)         2.2           Product Voltage (V)         230           Dimmable         No	ETIM Class EC001959 E-number FI 4741139 Warranty 3 years Luminous flux (Im) 250 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 2.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 15000	Fixture rating	Open
E-number FI       4741139         Warranty       3 years         Luminous flux (Im)       250         Colour temperature (K)       4000         Light colour       Cool White         CRI (Ra)       80         Colour Variation Initial (SDCM)       SDCM6         Photobiological Risk Group       RG1         Wattage (W)       2.2         Product Voltage (V)       230         Dimmable       No	E-number FI 4741139  Warranty 3 years  Luminous flux (Im) 250  Colour temperature (K) 4000  Light colour Cool White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM6  Photobiological Risk Group RG1  Wattage (W) 2.2  Product Voltage (V) 230  Dimmable No  Average life (Nominal) (h) 15000	General application	Hospitality, Residential & Consumer
Warranty 3 years Luminous flux (Im) 250 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 2.2 Product Voltage (V) 230 Dimmable No	Warranty 3 years Luminous flux (Im) 250 Colour temperature (K) 4000 Light colour Cool White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 2.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 15000	ETIM Class	EC001959
Luminous flux (Im)  Colour temperature (K)  Light colour  CRI (Ra)  Colour Variation Initial (SDCM)  Photobiological Risk Group  Wattage (W)  Product Voltage (V)  Dimmable  250  4000  80  Colour Variation Initial (SDCM)  SDCM6  RG1  Wattage (W)  2.2  Product Voltage (V)  No	Luminous flux (Im)  Colour temperature (K)  Light colour  CRI (Ra)  Colour Variation Initial (SDCM)  Photobiological Risk Group  Wattage (W)  Product Voltage (V)  Dimmable  Average life (Nominal) (h)  250  Cool White  Cool White  SDCM6  RG1  VSDCM6  PRG1  VSDCM6  RG1  VSDCM6  AU  SDCM6  AU	E-number FI	4741139
Colour temperature (K) 4000  Light colour Cool White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM6  Photobiological Risk Group RG1  Wattage (W) 2.2  Product Voltage (V) 230  Dimmable No	Colour temperature (K) 4000  Light colour Cool White  CRI (Ra) 80  Colour Variation Initial (SDCM) SDCM6  Photobiological Risk Group RG1  Wattage (W) 2.2  Product Voltage (V) 230  Dimmable No  Average life (Nominal) (h) 15000	Warranty	3 years
Light colour CRI (Ra) 80 Colour Variation Initial (SDCM) Photobiological Risk Group RG1 Wattage (W) 2.2 Product Voltage (V) 230 Dimmable No	Light colour CRI (Ra) Colour Variation Initial (SDCM) Photobiological Risk Group Wattage (W) Product Voltage (V) Dimmable Average life (Nominal) (h)  Cool White SDCM6 PRG1 VSDCM6 PAG1 VSDCM6 PRG1 VSDCM6 VSDCM6 PRG1 VSDCM6 VSDCM6 Photobiological Risk Group RG1 VSDCM6 V	Luminous flux (Im)	250
CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 2.2 Product Voltage (V) 230 Dimmable No	CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM6 Photobiological Risk Group RG1 Wattage (W) 2.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 15000	Colour temperature (K)	4000
Colour Variation Initial (SDCM)  Photobiological Risk Group  Wattage (W)  Product Voltage (V)  Dimmable  SDCM6  RG1  2.2  230  No	Colour Variation Initial (SDCM)  Photobiological Risk Group  RG1  Wattage (W)  2.2  Product Voltage (V)  Dimmable  Average life (Nominal) (h)  SDCM6  RG1  RG1  AU  AU  AU  BOUNG  SDCM6  RG1  AU  BOUNG  RG1  AU  BOUNG  RG1	Light colour	Cool White
Photobiological Risk Group RG1 Wattage (W) 2.2 Product Voltage (V) 230 Dimmable No	Photobiological Risk Group  Wattage (W)  Product Voltage (V)  Dimmable  Average life (Nominal) (h)  RG1  2.2  Product Voltage (V)  230  No  15000	CRI (Ra)	80
Wattage (W) 2.2 Product Voltage (V) 230 Dimmable No	Wattage (W) 2.2 Product Voltage (V) 230 Dimmable No Average life (Nominal) (h) 15000	Colour Variation Initial (SDCM)	SDCM6
Product Voltage (V) 230 Dimmable No	Product Voltage (V) 230  Dimmable No  Average life (Nominal) (h) 15000	Photobiological Risk Group	RG1
Dimmable No	Dimmable No Average life (Nominal) (h) 15000	Wattage (W)	2.2
	Average life (Nominal) (h) 15000	Product Voltage (V)	230
Average life (Nominal) (h) 15000		Dimmable	No
	Product EAN number 5/10288206661	Average life (Nominal) (h)	15000
Product EAN number 5410288296661	7410200290001	Product EAN number	5410288296661



# ToLEDo G9 ToLEDo Retro G9 CL 250LM 840 SL 0029666

### **PHOTOMETRY**



### **TECHNICAL DRAWINGS**

