

# PRODUCT DATASHEET SPC.T FR 15 W 230 V E14

SPECIAL T/OVEN | Incandescent lamps, tubular shape



#### Areas of application

- Baking ovens
- Domestic baking ovens




## **TECHNICAL DATA**

## Electrical data

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	230 V

## Photometrical data

Luminous flux	85 lm
Luminous efficacy	5 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	> 99
Light color	927



# Light technical data

		Starting time	0 s
--	--	---------------	-----

# **Dimensions & Weight**

Overall length	57.00 mm
Length with base excl. base pins/connection	57.00 mm
Light center length (LCL)	45,0 mm
Diameter	26,0 mm
Product weight	7.6 g

# Lifespan

Lifespan	1000 h

## Additional product data

Base (standard designation)	E14
Mercury-free	Yes

## **Capabilities**

Dimmable	Yes	
	. 65	

#### Certificates & Standards

Energy efficiency class	G
Energy consumption	15.00 kWh/1000h

# Country-specific categorizations

ILCOS	IBT/F-15-230-E14-26
Order reference	SPC.T26/57 FR 1

# Energy labelling regulation data acc EU 2019/2015

Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  E14  Connected light source (CLS)  No  Color-tuneable light source  Envelope  No  High luminance light source  Anti-glare shield  No  Correlated colour temperature type  SINGLE_VALUE  Standby power  0.00 W  Networked standby power for CLS  O W  Claim of equivalent power  No  Length  Height  26,0 mm  Width  Chromaticity coordinate x  0.496  Chromaticity coordinate y  0.412	
Light source cap-type (or other electric interface)  Connected light source (CLS)  No  Color-tuneable light source  Envelope  No  High luminance light source  No  Anti-glare shield  No  Correlated colour temperature type  SINGLE_VALUE  Standby power  0.00 W  Networked standby power for CLS  0 W  Claim of equivalent power  Length  Height  26,0 mm  Width  Chromaticity coordinate x  0.496  Chromaticity coordinate y  0.00  No	
Connected light source (CLS)  Color-tuneable light source  Envelope  No  High luminance light source  Anti-glare shield  Correlated colour temperature type  SINGLE_VALUE  Standby power  0.00 W  Networked standby power for CLS  Claim of equivalent power  Length  Height  26,0 mm  Width  Chromaticity coordinate x  0.496  Chromaticity coordinate y  No	
Color-tuneable light source  Envelope  No  High luminance light source  No  Anti-glare shield  Correlated colour temperature type  SINGLE_VALUE  Standby power  0.00 W  Networked standby power for CLS  0 W  Claim of equivalent power  Length  55.00 mm  Height  26,0 mm  Width  26,0 mm  Chromaticity coordinate x  0.496  Chromaticity coordinate y  0.412	
Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Standby power 0.00 W Networked standby power for CLS 0 W Claim of equivalent power No Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.412	
High luminance light source  Anti-glare shield  No  Correlated colour temperature type  SINGLE_VALUE  Standby power  0.00 W  Networked standby power for CLS  0 W  Claim of equivalent power  No  Length  55.00 mm  Height  26,0 mm  Width  26,0 mm  Chromaticity coordinate x  0.496  Chromaticity coordinate y  0.412	
Anti-glare shield  Correlated colour temperature type  SINGLE_VALUE  Standby power  0.00 W  Networked standby power for CLS  0 W  Claim of equivalent power  No  Length  55.00 mm  Height  26,0 mm  Width  26,0 mm  Chromaticity coordinate x  0.496  Chromaticity coordinate y  0.412	
Correlated colour temperature type  SINGLE_VALUE  Standby power  0.00 W  Networked standby power for CLS  0 W  Claim of equivalent power  No  Length  55.00 mm  Height  26,0 mm  Width  26,0 mm  Chromaticity coordinate x  0.496  Chromaticity coordinate y  0.412	
Standby power 0.00 W  Networked standby power for CLS 0 W  Claim of equivalent power No  Length 55.00 mm  Height 26,0 mm  Width 26,0 mm  Chromaticity coordinate x 0.496  Chromaticity coordinate y 0.412	
Networked standby power for CLS 0 W  Claim of equivalent power No  Length 55.00 mm  Height 26,0 mm  Width 26,0 mm  Chromaticity coordinate x 0.496  Chromaticity coordinate y 0.412	
Claim of equivalent power  Length  55.00 mm  Height  26,0 mm  Width  26,0 mm  Chromaticity coordinate x  0.496  Chromaticity coordinate y  0.412	
Length55.00 mmHeight26,0 mmWidth26,0 mmChromaticity coordinate x0.496Chromaticity coordinate y0.412	
Height 26,0 mm  Width 26,0 mm  Chromaticity coordinate x 0.496  Chromaticity coordinate y 0.412	
Width 26,0 mm  Chromaticity coordinate x 0.496  Chromaticity coordinate y 0.412	
Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.412	
Chromaticity coordinate y 0.412	
Beam angle correspondence SPHERE_360	
EPREL ID 714462	
Model number AC35397	

#### **DOWNLOAD DATA**

## Photometric and lighting design files



Spectral power distribution

#### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300003085	Folding box 1	61 mm x 24 mm x 27 mm	14.60 g	0.04 dm <sup>3</sup>
4050300555171	Bundle 10	56 mm x 63 mm x 137 mm	129.00 g	0.48 dm³
4050300555188	Shipping box 100	275 mm x 141 mm x 138 mm	1490.00 g	5.35 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.