# PRODUCT DATASHEET ENDURA Classic Calice Wall E27

ENDURA CLASSIC CALICE | Stainless steel luminaires with glass diffuser



#### Areas of application

- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

#### **Product benefits**

- High flexibility in the choice of the light source thanks to E27 base
- Easy and quick installation

#### **Product features**

- Available with and without motion sensor
- Stainless steel housing
- Type of protection: IP44



# **TECHNICAL DATA**


# Electrical data

| Nominal voltage        | 220240 V      |
|------------------------|---------------|
| Mains frequency        | 5060 Hz       |
| Power factor $\lambda$ | > 0.50        |
| Protection class       | T.            |
| Operating mode         | Mains voltage |

#### Photometrical data

# **Dimensions & Weight**

| Length         | 161.00 mm |
|----------------|-----------|
| Width          | 120.00 mm |
| Height         | 290.00 mm |
| Product weight | 900.00 g  |



# Materials & Colors

| Product color   | Steel           |
|-----------------|-----------------|
| Housing color   | Steel           |
| Body material   | Stainless steel |
| Cover material  | Glass           |
| Mercury content | 0.0 mg          |

# **Application & Mounting**

| Ambient temperature range | -20+40 °C                   |  |
|---------------------------|-----------------------------|--|
| Type of connection        | Terminal, 3-Pole (L, N, PE) |  |



| Type of protection      | IP44            |
|-------------------------|-----------------|
| Dimmable                | No              |
| Mounting type           | Surface         |
| Mounting location       | Wall            |
| Application environment | Outdoor         |
| LED module replaceable  | Not replaceable |
| With light source       | No              |

#### Certificates & Standards

| Standards  | CE / EAC / UKCA |  |
|--|-----------------|--|
| Luminaire with limited surface temperature, "D sign" | No              |  |

#### Additional product data

|  | Product remar | k | Maximum bulb wattage: 60 W |
|--|---------------|---|----------------------------|
|--|---------------|---|----------------------------|

# **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

#### **DOWNLOAD DATA**

|     | Documents and certificates      |
|-----|---------------------------------|
| PDF | User instruction                |
| PDF | Declarations Of Conformity CE   |
| PDF | Declarations Of Conformity UKCA |

### **LOGISTICAL DATA**

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075477957 | Folding box<br>1             | 202 mm x 162 mm x 334 mm             | 1055.00 g    | 10.93 dm <sup>3</sup> |
| 4058075477964 | Shipping box<br>4            | 420 mm x 350 mm x 340 mm             | 4997.00 g    | 49.98 dm³             |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.



# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.