



The spray-proof and impact-resistant surface-mounted luminaires from the Prolumia Rockdisc III series meet the lighting needs in outdoor areas in non-residential and housing construction. Both normal and semi-shielded versions are optionally available with a microwave sensor, large sizes also with emergency function. Simply set the desired color temperature and light output by means of DIP switches. In addition, luminaires with and without sensor can effortlessly be configured as master/slave.

SPRAY-PROOF AND IMPACT-RESISTANT SURFACE-MOUNTED
LUMINAIRE (IP66 & IK10) WITH BLACK POWDER-COATED ALUMINIUM
HOUSING AND COVER MADE OF SELF-EXTINGUISHING
IMPACT-RESISTANT POLYCARBONATE

MICROWAVE SENSOR WITH ADJUSTABLE DETECTION RANGE, POWER/STANDBY TIME AND DAYLIGHT LEVEL OPTIONAL

**3-STEP DIMMING OPTION (100% → 10%/25% → 0%)** 

DAYLIGHT PRIORITY: POSSIBLE TO SWITCH ON/OFF BASED UPON DAYLIGHT

**SWITCHABLE COLOR TEMPERATURE AND LIGHT OUTPUT** 

## **DIFFERENT VERSIONS AVAILABLE:**

NORMAL AND SEMI-SHIELDED VERSION IN 2 DIFFERENT SIZES / STANDARD / MICROWAVE SENSOR / EMERGENCY FUNCTION / EMERGENCY FUNCTION + MICROWAVE SENSOR

# **SPECIFICATIONS**

Light source: SMD 2835 LED

Beam angle: 120°

Switchable color temperature: 3000K/4000K

Light output: Switchable

Operating temperature:  $-25^{\circ}\text{C} - +50^{\circ}\text{C}$ (MW sensor:  $-25^{\circ}\text{C} - +40^{\circ}\text{C}$  / Emergency mode:  $-10^{\circ}\text{C} - +50^{\circ}\text{C}$  / Emergency mode + MW sensor:

-10°C - +40°C)

Rated life hours: L80B10 > 100,000

LED driver (included): CE

Supply voltage: 220-240V AC 50/60Hz

Power factor: > 0.90

Electrical safety class: Class I

Master/slave: Yes

Emergency mode version:

Battery: Ni-Cd 7.2V Autonomy: 1 hour

# **APPLICATIONS**

PUBLIC AREAS, PORCHES, STAIRCASES, ETC.
















# **ROCKDISC III**

2 different sizes
Optional with MW sensor, Emergency mode
and Emergency mode + MW sensor

Art. no.	Description	Price
Rockdisc III Mini, ø270x74mm, 3000K/4000K, switchable light output		
40009060 📀	Standard, 9W, 800Lm/400Lm	€75
40009061	+ MW sensor, 10.5W, 800Lm/400Lm	€97
Rockdisc III, ø340x83mm, 3000K/4000K, switchable light output		
40009070 📀	Standard, 23W, 2000Lm/1300Lm/900Lm	€115
40009071	+ MW sensor, 24W, 2000Lm/1300Lm/900Lm	€138
40009072	+ Emergency mode, 23.5W, 2000Lm/1300Lm/900Lm	€149
40009073	+ Emergency mode + MW sensor, 24.5W, 2000Lm/1300Lm/900Lm	€172



# **ROCKDISC III** SEMI-SHIELDED

2 different sizes
Optional with MW sensor, Emergency mode
and Emergency mode + MW sensor

Art. no.	Description	Price	
Rockdisc III Mini Semi-shielded, ø270x74mm, 3000K/4000K, switchable light output			
40009062 🕜	Standard, 9W, 650Lm/330Lm	€82	
40009063 🕜	+ MW sensor, 10.5W, 650Lm/330Lm	€ 103	
Rockdisc III Semi-shielded, ø340x83mm, 3000K/4000K, switchable light output			
40009075 🕜	Standard, 23W, 1600Lm/1000Lm/700Lm	€122	
40009076 🕜	+ MW sensor, 24W, 1600Lm/1000Lm/700Lm	€ 145	
40009077	+ Emergency mode, 23.5W, 1600Lm/1000Lm/700Lm	€ 156	
40009078	+ Emergency mode + MW sensor, 24.5W, 1600Lm/1000Lm/700Lm	€ 179	



# PROLUMIA®

## **PROLUMIA NL**

Riga 10 2993 LW BARENDRECHT **T** +31 (0)180 64 54 00 **E** info@prolumia.nl

## **PROLUMIA BE**

Prins Boudewijnlaan 49 2650 EDEGEM T +32 (0)3 826 99 99 E info@prolumia.be

## **PROLUMIA CZ**

Ke Slivenci 48 154 00 PRAHA 5 - LOCHKOV T +420 222 563 003 E info@prolumia.cz

## **PROLUMIA DE**

Heinz-Bäcker-Str. 27 45356 ESSEN **T** +49 (0)201 560503 50 **E** info@prolumia.de

MORE INFO ABOUT ROCKDISC III ONLINE:



Version: 1.0 - 2022-04

Nedelko B.V. pays the utmost attention to its catalog and reliability and actuality of the information contained therein. Despite all care, inaccuracies and omissions can not always be prevented. Nedelko B.V. is not liable for errors or inaccuracies. For the most current information please contact our sales department.