

Product data sheet

Item No. 91.232.6004.2

Cable assembly GST15I3KS-S 15 W 60WS

geis® Connection cable male - free end; length: 6m; type GST15I3; 3-pole; 250 V / 16 A; colour of coding: white with white strain-relief; cable: H05VV-F 3G1,5, colour: white



Item No.	91.232.6004.2
EAN	4015573837737
Order Unit	10 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	White
Marking of poles	
Color of housing inclusive strain relief	White

Model

Number of poles	3
Nominal cross section conductor	1.5 mm²
Degree of protection (IP)	IP40
Wire strip length	8 mm
sheath strip length	21 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F

Cable colour	White
Cable diameter	8.3 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST15i3 plug
Version cable end 2	Free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	6 m
--------------	-----

Technical drawing

Steckerteil/male connection

Gesamtlänge / total length

Kabel/cable H05VV-F3G1,5
Farbe/colour: siehe Tabelle/see table

.F	Farbe colour	Codierung Stacker male	Farbe colour
.1	schwarz black		schwarz black
.2	weiß white		weiß white

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
91.232.XX04.F	XX in dm-Schritten	91.232.1004.1 = 10dm/L= 1000mm	GST15i3KS-S 15 10SW
U1.232.XX04.F	XX in m-Schritten	U1.232.1204.1 = 12 m/L=12000mm	GST15i3KS-S 15 X12SW

Typ/type: GST15i3KS-S 15 .. SW = schwarz/black
WS = weiß/white

Further data see catalog
further data see catalog