

## Product data sheet

Item No. 91.222.5000.1

### Cable assembly GST15I2KSBS 15 W 50SW

gesis® Extension cable female - male; length: 5m; type GST15I2;  
2-pole; 250 V / 16 A; colour of coding: black with black strain-relief;  
cable: H05VV-F 2x1,5, colour: black



|            |               |
|------------|---------------|
| Item No.   | 91.222.5000.1 |
| EAN        | 4049644009204 |
| Order Unit | 20 Piece(s)   |

## Certificates / Approvals

### Technical data

#### General

|                                          |        |
|------------------------------------------|--------|
| Rated current                            | 16 A   |
| Rated voltage                            | 250 V  |
| Rated impulse voltage                    | 4 kV   |
| Pollution degree                         | 2      |
| Mechanical coding                        | Code 1 |
| Interlockable                            | Yes    |
| Color of coding/ contact carrier         | Black  |
| Marking of poles                         |        |
| Color of housing inclusive strain relief | Black  |

#### Model

|                                 |                  |
|---------------------------------|------------------|
| Number of poles                 | 2                |
| Nominal cross section conductor | 1.5 mm²          |
| Degree of protection (IP)       | IP40             |
| Cable type                      | H05VV-F          |
| Cable colour                    | Black            |
| Cable diameter                  | 7.5 mm           |
| Version of cable                | Female - male    |
| Type of cord set                | Connecting cable |
| Version cable end 1             | female           |

|                          |                     |
|--------------------------|---------------------|
| Version cable end 2      | male                |
| Cross section of cable 2 | 1.5 mm <sup>2</sup> |

**Material**

|                                              |               |
|----------------------------------------------|---------------|
| Surface finish                               | Silver-plated |
| Halogen free                                 | No            |
| Continuous temperature of cable              | 70 °C         |
| Insulation components continuous temperature | 100 °C        |

**Dimensions**

|              |     |
|--------------|-----|
| Total length | 5 m |
|--------------|-----|