

Product data sheet

Item No. 91.921.3453.0

Female connector with strain relief GST15i2S B1 ZR1WW PB01

Connector GST15i2, 2 pole, female, screw connection, 250V/6A,
color of coding: pastel blue, color of housing: black



Item No.	91.921.3453.0
EAN	4015573915992
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	6 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	2
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Pastel blue
Marking of poles	
Color of housing inclusive strain relief	White

Connection Data

Cable diameter	7.7 mm
Cable diameter 2	6 mm
Connection cross section solid	1.5 mm ²
Cross section solid 2	0.5 mm ²
Connection cross section stranded	1.5 mm ²
Cross section stranded 2	0.5 mm ²

Terminations per pole	1
-----------------------	---

Model

Model	female
Number of poles	2
Connection type	Screw connection
Degree of protection (IP)	IP40

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	53.2 mm
Width	17.7 mm
Height	13.8 mm