

## Product data sheet

Item No. 91.222.5060.9

### Cable assembly GST15I2KSBS 15HW 50PB01

geis® Extension cable female - male; length: 5m; type GST15I2;  
2-pole; 250 V / 16 A; colour of coding: pastel blue with white strain-  
relief; cable: H05Z1Z1-F 2x1,5 , colour: white



|            |               |
|------------|---------------|
| Item No.   | 91.222.5060.9 |
| EAN        | 4015573924918 |
| Order Unit | 20 Piece(s)   |

## Certificates / Approvals

### Technical data

#### General

|                                          |             |
|------------------------------------------|-------------|
| Rated current                            | 6 A         |
| Rated voltage                            | 250 V       |
| Rated impulse voltage                    | 4 kV        |
| Pollution degree                         | 2           |
| Mechanical coding                        | Yes         |
| Interlockable                            | Yes         |
| Color of coding/ contact carrier         | Pastel blue |
| Marking of poles                         |             |
| Color of housing inclusive strain relief | White       |

#### Model

|                                 |                  |
|---------------------------------|------------------|
| Number of poles                 | 2                |
| Nominal cross section conductor | 1.5 mm²          |
| Degree of protection (IP)       | IP40             |
| Cable type                      | S05HH-F          |
| Cable colour                    | White            |
| Cable diameter                  | 7.5 mm           |
| Version of cable                | Female - male    |
| Type of cord set                | Connecting cable |
| Version cable end 1             | GST15i2 socket   |

|                     |              |
|---------------------|--------------|
| Version cable end 2 | GST15i2 plug |
|---------------------|--------------|

**Material**

|                                              |               |
|----------------------------------------------|---------------|
| Surface finish                               | Silver-plated |
| Halogen free                                 | Yes           |
| Continuous temperature of cable              | 70 °C         |
| Insulation components continuous temperature | 100 °C        |

**Dimensions**

|              |     |
|--------------|-----|
| Total length | 5 m |
|--------------|-----|