

## Product data sheet

Item No. 91.232.7060.1

### Cable assembly GST15I3KSBS 15HW 70SW

geis® Extension cable female - male; length: 7m; type GST15I3;  
3-pole; 250 V / 16 A; colour of coding: black with black strain-relief;  
cable: H05Z1Z1-F 3G1,5 , colour: black



|            |               |
|------------|---------------|
| Item No.   | 91.232.7060.1 |
| EAN        | 4049644009549 |
| Order Unit | 10 Piece(s)   |

## Certificates / Approvals



## Technical data

### General

|                                          |        |
|------------------------------------------|--------|
| Rated current                            | 16 A   |
| Rated voltage                            | 250 V  |
| Rated impulse voltage                    | 4 kV   |
| Pollution degree                         | 2      |
| Mechanical coding                        | Code 1 |
| Interlockable                            | Yes    |
| Color of coding/ contact carrier         | Black  |
| Marking of poles                         |        |
| Color of housing inclusive strain relief | Black  |

### Model

|                                 |               |
|---------------------------------|---------------|
| Number of poles                 | 3             |
| Nominal cross section conductor | 1.5 mm²       |
| Degree of protection (IP)       | IP40          |
| Cable type                      | S05Z1Z1-F     |
| Cable colour                    | Black         |
| Cable diameter                  | 8 mm          |
| Version of cable                | Female - male |

|                     |                  |
|---------------------|------------------|
| Type of cord set    | Connecting cable |
| Version cable end 1 | GST15i3 socket   |
| Version cable end 2 | GST15i3 plug     |

**Material**

|                                              |               |
|----------------------------------------------|---------------|
| Surface finish                               | Silver-plated |
| Halogen free                                 | Yes           |
| Continuous temperature of cable              | 70 °C         |
| Insulation components continuous temperature | 100 °C        |

**Dimensions**

|              |     |
|--------------|-----|
| Total length | 7 m |
|--------------|-----|