

Product data sheet

Item No. 92.207.4063.3

Cable assembly GST18I4KSB- 15H 40GR01

geis® Connection cable female - free end; length: 4m; type GST18I4; 4-pole; 250/400 V / 16 A; colour of coding: grey with black strain-relief; cable: H05Z1Z1-F 4G1,5, colour: black



Item No.	92.207.4063.3
EAN	4015573853768
Order Unit	15 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 2
Interlockable	Yes
Color of coding/ contact carrier	Pebble gray
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	4
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP40
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05Z1Z1-F

Cable colour	Black
Cable diameter	9.2 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	GST1814 socket
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	Yes
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	4 m
--------------	-----

Technical drawing

Buchenteil/female connector

Kabel/cable: H05Z1Z1-F4G1,5 halogenfrei/halogenfree
Farbe/colour: siehe Tabelle/see table

Pol/pole	Aderfarbe/colour of core
L2	schwarz/black
N	blau/blue
⊕	grün-gelb/green-yellow
L1	brown/brown

.F	Farbe colour	Codierung *X*	Kabelfarbe / cable colour	Zugentlastungsfarbe/strain relief colour
.1	schwarz black	2 N PE 1	schwarz black	schwarz black
.2	weiß white	2 N PE 1	weiß white	weiß white
.3	grau grey	2 N PE 1	schwarz black	schwarz black

Teile-Nr. part-no. L Beispiel (Farbe: schwarz) example (colour: black) Typ type

92.207.XX63.F XX in dm-Schritten 92.207.1063.1 = 10dm/L = 1000mm GST1814KSB- 15H 10SW

U2.207.XX63.F XX in m-Schritten U2.207.1263.1 = 12 m/L=12000mm GST1814KSB- 15H X10SW

Freitoleranz nach General tolerance 100 - Zeichnung, keine massiven Änderungen 100 - drawing, no mass modifications allowed 1 - Verwendung First use

Zeichnung Nr./Drawing No. 92.207.1063.1 01K

Typ/type: GST1814KSB- 15H.. SW = schwarz/black WS = weiß/white GR01 = grau/grey

Wieland

PRE-ASSEMBLED CABLE KONFERT-LEITUNG Buchse/female-frees Ende/free end HALOGEN-FREE Schraubanschluss/screw connection 1,5gmm 250V