

Product data sheet

Item No. 91.952.9053.0

Male connector GST15I5S S1 R V WS

Device connectors, snap-in panel mount, GST15i5, 5 pole, male, screw connection, 250/400V, 16A, material thickness 0,5 - 1,5 mm, color of coding: white, color of frame: white



Item No.	91.952.9053.0
EAN	4015573918214
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	400 V
Rated voltage 2	250 V
Pollution degree	2
Mechanical coding	Code 1
Rated impulse voltage	4 kV
Interlockable	Yes
Color of coding/ contact carrier	White
Marking of poles	
Color of separate adapter (if present)	White

Connection Data

Connection cross section solid	2.5 mm²
Cross section solid 2	0.5 mm²
Connection cross section stranded	2.5 mm²
Cross section stranded 2	0.5 mm²
Terminations per pole	1

Model

Model	male
Number of poles	5
Connection type	Screw connection
Connecting thread metric	M3
Angle of plug	Straight
Degree of protection (IP)	IP40
Thickness of housings (electrical device) 2	0.5 mm
Thickness of housings (electrical device)	1.5 mm
Built-in component	Snap-in/screw-in

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	31.2 mm
Width	34.6 mm
Height	19.6 mm

Technical drawing

