

Product data sheet

Item No. 92.032.8758.1

Male connector GST18i3S S1 R V SW

Device connectors, snap-in panel mount, GST18i3, 3 pole, male, screw connection, 250 V, 20 A, material thickness 0,5 - 1,5 mm, colour of coding: black



Item No.	92.032.8758.1
EAN	4015573455597
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Pollution degree	2
Mechanical coding	Code 1
Rated impulse voltage	4 kV
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	

Connection Data

Connection cross section solid	2.5 mm²
Cross section solid 2	0.5 mm²
Connection cross section stranded	2.5 mm²
Cross section stranded 2	0.5 mm²
Terminations per pole	1

Model

Model	male
-------	------

Number of poles	3
Connection type	Screw connection
Connecting thread metric	M3
Angle of plug	Straight
Degree of protection (IP)	IP40
Thickness of housings (electrical device) 2	0.5 mm
Thickness of housings (electrical device)	1.5 mm
Built-in component	Snap-in

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Tin-plated

Dimensions

Length	30.3 mm
Width	32.8 mm
Height	21 mm

Technical drawing

