



Product data sheet

Item No. 91.932.9053.0

Male connector GST15I3S S1 R W WS

Device connectors, snap-in panel mount, GST15i3, 4 pole, male, screw connection, 250V/16A, material thickness 0,5 - 1,5 mm, color of coding: white, color of frame: white



Item No.	91.932.9053.0
EAN	4015573833852
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Retail surrent	16 A
Rated current	10 A
Rated voltage	250 V
Pollution degree	2
Mechanical coding	Code 1
Rated impulse voltage	4 kV
Interlockable	Yes
Color of coding/ contact carrier	White
Marking of poles	
Color of separate adapter (if present)	White

Connection Data

Connection cross section solid	2.5 mm ²
Cross section solid 2	0.5 mm ²
Connection cross section stranded	2.5 mm ²
Cross section stranded 2	0.5 mm ²
Terminations per pole	1





Model

Model	male
Number of poles	3
Connection type	Screw connection
Connecting thread metric	M3
Angle of plug	Straight
Degree of protection (IP)	IP40
Thickness of housings (electrical device) 2	0.5 mm
Thickness of housings (electrical device)	1.5 mm
Built-in component	Snap-in/screw-in

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	30.2 mm
Width	22 mm
Height	19.6 mm









