

## Product data sheet

Item No. 92.207.1060.1

### Cable assembly GST18I4KSBS 15H 10SW

geis® Extension cable female - male; length: 1m; type GST18I4;  
4-pole;250/400 V / 16 A; colour of coding: black with black strain-  
relief; cable: H05Z1Z1-F 4G1,5, colour: black



|            |               |
|------------|---------------|
| Item No.   | 92.207.1060.1 |
| EAN        | 4015573664623 |
| Order Unit | 50 Piece(s)   |

## Certificates / Approvals



## Technical data

### General

|                                          |        |
|------------------------------------------|--------|
| Rated current                            | 16 A   |
| Rated voltage                            | 400 V  |
| Rated impulse voltage                    | 4 kV   |
| Pollution degree                         | 2      |
| Mechanical coding                        | Code 1 |
| Interlockable                            | Yes    |
| Color of coding/ contact carrier         | Black  |
| Marking of poles                         |        |
| Color of housing inclusive strain relief | Black  |

### Model

|                                 |               |
|---------------------------------|---------------|
| Number of poles                 | 4             |
| Nominal cross section conductor | 1.5 mm²       |
| Degree of protection (IP)       | IP40          |
| Cable type                      | H05Z1Z1-F     |
| Cable colour                    | Black         |
| Cable diameter                  | 9.2 mm        |
| Version of cable                | Female - male |

|                     |                  |
|---------------------|------------------|
| Type of cord set    | Connecting cable |
| Version cable end 1 | GST18i4 socket   |
| Version cable end 2 | GST18i4 plug     |

#### Material

|                                              |            |
|----------------------------------------------|------------|
| Surface finish                               | Tin-plated |
| Halogen free                                 | Yes        |
| Continuous temperature of cable              | 70 °C      |
| Insulation components continuous temperature | 100 °C     |

#### Dimensions

|              |     |
|--------------|-----|
| Total length | 1 m |
|--------------|-----|

#### Technical drawing

