

Product data sheet

Item No. 92.207.8003.3

Cable assembly GST18I4KSB- 15 80GR01

geis® Connection cable female - free end; length: 8m; type GST18I4; 4-pole; 250/400 V / 16 A; colour of coding: grey with black strain-relief; cable: H05VV-F 4G1,5, colour: black



Item No.	92.207.8003.3
EAN	4015573854000
Order Unit	5 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 2
Interlockable	Yes
Color of coding/ contact carrier	Pebble gray
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	4
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP40
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F

Cable colour	Black
Cable diameter	9.2 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	GST18i4 socket
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	8 m
--------------	-----

Technical drawing

⑤ Kabel/cable: H05VV-F4G1,5
Farbe/colour: siehe Tabelle/see table

Pol pole	Aderfarbe colour of core
L2	schwarz / black
N	blau / blue
⊕	grün-gelb / green-yellow
L1	braun / brown

.F Farbe colour	Codierung +X Buchse female	Kabelfarbe / cable colour Zugentlastungsfarbe/strain relief colour
.1 schwarz black	2 N PE 1	schwarz black
.2 weiß white	2 N PE 1	weiß white
.3 grau grey	2 N PE 1	schwarz black

Teile-Nr.
part-no.

L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.207.XX03.F	XX in dm-Schritten 92.207.1003.1 = 10dm/L = 1000mm	GST18i4KSB- 15 10SW
U2.207.XX03.F	XX in m-Schritten U2.207.1203.1 = 12 m/L=12000mm	GST18i4KSB- 15 X10SW

Typ/type: GST18i4KSB- 15 ..WS = schwarz/black
GR01 = weiß/white
GR01 = grau/grey

Weitere Daten siehe Katalog
further data see catalog

Zeichnung Nr./Drawing No.	92.207.0503.1 01K f
PRE-ASSEMBLED CABLE KONFEKT-LEITUNG	
Buchse/female freies Ende/free end 1,5mm Schraubanschluß/screw connection 250V	