

## Product data sheet

Item No. 92.207.6000.3

### Cable assembly GST18I4KSBS 15 60GR01

geis® Extension cable female - male; length: 6m; type GST18I4;  
4-pole; 250/400 V / 16 A; colour of coding: grey with black strain-  
relief; cable: H05VV-F 4G1,5, colour: black



|            |               |
|------------|---------------|
| Item No.   | 92.207.6000.3 |
| EAN        | 4015573569508 |
| Order Unit | 10 Piece(s)   |

## Certificates / Approvals



## Technical data

### General

|                                          |             |
|------------------------------------------|-------------|
| Rated current                            | 16 A        |
| Rated voltage                            | 400 V       |
| Rated impulse voltage                    | 4 kV        |
| Pollution degree                         | 2           |
| Mechanical coding                        | Code 2      |
| Interlockable                            | Yes         |
| Color of coding/ contact carrier         | Pebble gray |
| Marking of poles                         |             |
| Color of housing inclusive strain relief | Black       |

### Model

|                                 |                     |
|---------------------------------|---------------------|
| Number of poles                 | 4                   |
| Nominal cross section conductor | 1.5 mm <sup>2</sup> |
| Degree of protection (IP)       | IP40                |
| Cable type                      | H05VV-F             |
| Cable colour                    | Black               |
| Cable diameter                  | 9.2 mm              |
| Version of cable                | Female - male       |

|                     |                  |
|---------------------|------------------|
| Type of cord set    | Connecting cable |
| Version cable end 1 | GST18i4 socket   |
| Version cable end 2 | GST18i4 plug     |

#### Material

|                                              |            |
|----------------------------------------------|------------|
| Surface finish                               | Tin-plated |
| Halogen free                                 | No         |
| Continuous temperature of cable              | 70 °C      |
| Insulation components continuous temperature | 100 °C     |

#### Dimensions

|              |     |
|--------------|-----|
| Total length | 6 m |
|--------------|-----|

#### Technical drawing

