

## Product data sheet

Item No. 92.232.2010.3

### Cable assembly GST18i3K1BS 15W 20GR01

gesis® Extension cable female - male; length: 2m; type GST18i3;  
3-pole; 250 V / 16 A; colour of coding: grey with grey strain-relief;  
cable: H05V2V2-F 3G1,5, colour: black



|            |               |
|------------|---------------|
| Item No.   | 92.232.2010.3 |
| EAN        | 4015573854482 |
| Order Unit | 50 Piece(s)   |

## Certificates / Approvals

### Technical data

#### General

|                                          |             |
|------------------------------------------|-------------|
| Rated current                            | 16 A        |
| Rated voltage                            | 250 V       |
| Rated impulse voltage                    | 4 kV        |
| Pollution degree                         | 2           |
| Mechanical coding                        | Code 2      |
| Interlockable                            | Yes         |
| Color of coding/ contact carrier         | Pebble gray |
| Marking of poles                         |             |
| Color of housing inclusive strain relief | Pebble gray |

#### Model

|                                 |                  |
|---------------------------------|------------------|
| Number of poles                 | 3                |
| Nominal cross section conductor | 1.5 mm²          |
| Degree of protection (IP)       | IP40             |
| Cable type                      | H05V2V2-F        |
| Cable colour                    | Black            |
| Cable diameter                  | 8.3 mm           |
| Version of cable                | Female - male    |
| Type of cord set                | Connecting cable |
| Version cable end 1             | GST18i3 socket   |

|                     |              |
|---------------------|--------------|
| Version cable end 2 | GST18i3 plug |
|---------------------|--------------|

#### Material

|                                             |            |
|---------------------------------------------|------------|
| Surface finish                              | Tin-plated |
| Halogen free                                | No         |
| Continuous temperature of cable             | 90 °C      |
| Insulation components continous temperature | 100 °C     |

#### Dimensions

|              |     |
|--------------|-----|
| Total length | 2 m |
|--------------|-----|

#### Technical drawing

