

## Product data sheet

Item No. 92.232.5007.2

### Cable assembly

gesis® Mains connection cable female - Schuko plug; length: 5m;  
type GST18I3; 3-pole; 250 V / 16 A; colour of coding: white with  
white strain-relief; cable: H05VV-F 3G1,5, colour: white



|            |               |
|------------|---------------|
| Item No.   | 92.232.5007.2 |
| EAN        | 4015573562301 |
| Order Unit | 20 Piece(s)   |

### Certificates / Approvals



### Technical data

#### General

|                                          |        |
|------------------------------------------|--------|
| Rated current                            | 16 A   |
| Rated voltage                            | 250 V  |
| Rated impulse voltage                    | 4 kV   |
| Pollution degree                         | 2      |
| Mechanical coding                        | Code 1 |
| Interlockable                            | Yes    |
| Color of coding/ contact carrier         | White  |
| Marking of poles                         |        |
| Color of housing inclusive strain relief | White  |

#### Model

|                                 |                     |
|---------------------------------|---------------------|
| Number of poles                 | 3                   |
| Nominal cross section conductor | 1.5 mm <sup>2</sup> |
| Degree of protection (IP)       | IP20                |
| Cable type                      | H05VV-F             |
| Cable colour                    | White               |
| Cable diameter                  | 8.3 mm              |
| Version of cable                | Female - male       |

|                     |                        |
|---------------------|------------------------|
| Type of cord set    | Mains connection cable |
| Version cable end 1 | GST18i3 socket         |
| Version cable end 2 | SchuKo plug            |

**Material**

|                                              |            |
|----------------------------------------------|------------|
| Surface finish                               | Tin-plated |
| Halogen free                                 | No         |
| Continuous temperature of cable              | 70 °C      |
| Insulation components continuous temperature | 100 °C     |

**Dimensions**

|              |     |
|--------------|-----|
| Total length | 5 m |
|--------------|-----|