



Product data sheet

Item No. 92.934.0153.0

Male connector with strain relief GST18I3F S2 ZR1 GR01

Connector GST18i3, 3 pole, male, spring clamp connection, 250 V, 20 A, colour of coding: pebble grey, colour of housing: black



Item No.	92.934.0153.0
EAN	4015573410541
Order Unit	50 Piece(s)

Certificates / Approvals



Technical data

General

20 A
250 V
4 kV
Yes
2
Code 2
Yes
Pebble gray
Black

Connection Data

Cable diameter	10.3 mm
Cable diameter 2	7.8 mm
Connection cross section solid	2.5 mm ²
Cross section solid 2	0.5 mm ²
Connection cross section stranded	1.5 mm ²
Cross section stranded 2	0.5 mm ²





Terminations per pole	2	
Model		
Model	male	
Number of poles	3	
Connection type	Tension clamp connection	
Degree of protection (IP)	IP40	
Remark to type of connection	Finely stranded con. req. Wieland cable end sleeve	
Material Control of the Control of t		
Housing material	Polyamide	
Halogen free	Yes	
Contact material	CuZn	
Insulation components continous temperature	100 °C	
Surface finish	Tin-plated	
Dimensions		
Length	75 mm	
Width	32.5 mm	
Height	15.5 mm	

Technical drawing

