

Product data sheet

Item No. 92.943.3053.1

Female connector with strain relief GST18i4S B1 ZR1 SW

Connector GST18i4, 4 pole, female, screw connection, 250 V, 20 A, colour of coding: black, colour of housing: black



Item No.	92.943.3053.1
EAN	4015573785656
Order Unit	50 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Connection Data

Cable diameter	12 mm
Cable diameter 2	6.5 mm
Connection cross section solid	2.5 mm²
Cross section solid 2	0.5 mm²
Connection cross section stranded	2.5 mm²
Cross section stranded 2	0.5 mm²

Terminations per pole	1
-----------------------	---

Model

Model	female
Number of poles	4
Connection type	Screw connection
Degree of protection (IP)	IP40

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Tin-plated

Dimensions

Length	69.4 mm
Width	38 mm
Height	15 mm



