



Product data sheet

Item No. 92.954.4453.0

Male connector with strain relief GST18I5S S1 ZR1 S PB02



Item No.	92.954.4453.0
EAN	4015573960947
Order Unit	50 Piece(s)



Technical data

General Rated current 20 A Rated voltage 250 V Rated impulse voltage 4 kV Pull relief Yes 2 Pollution degree Mechanical coding Code 2 Interlockable Yes Color of coding/ contact carrier Pastel blue Marking of poles Color of housing inclusive strain relief Black **Connection Data** 12.5 mm Cable diameter

Cable diameter	12.5 mm
Cable diameter 2	8.5 mm
Connection cross section solid	2.5 mm ²
Cross section solid 2	0.75 mm²
Connection cross section stranded	2.5 mm ²
Cross section stranded 2	0.5 mm²

💎 wieland



Terminations per pole	1	
Model		
Model	male	
Number of poles	5	
Connection type	Screw connection	
Degree of protection (IP)	IP20	

Finely stranded con. req. Wieland cable end sleeve

Material

Remark to type of connection

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Tin-plated

Dimensions

Length	76.4 mm
Width	47.75 mm
Height	15 mm

Technical drawing

