

Product data sheet

Item No. 92.232.5004.5

Cable assembly GST18I3K1-S 15 50RT03

geis® Connection cable male - free end; length: 5m; type GST18I3; 3-pole; 250 V / 16 A; colour of coding: red with red strain-relief; cable: H05VV-F 3G1,5, colour: black



Item No.	92.232.5004.5
EAN	4015573680494
Order Unit	20 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 3
Interlockable	Yes
Color of coding/ contact carrier	Salmon pink
Marking of poles	
Color of housing inclusive strain relief	Salmon pink

Model

Number of poles	3
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP40
Wire strip length	9 mm
sheath strip length	37 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F

Cable colour	Black
Cable diameter	8.3 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST18i3 plug
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	5 m
--------------	-----

Technical drawing

Kabel/cable H05VV-F3G1,5
Farbe/colour: siehe Tabelle/see table

.F	Farbe colour	Codierung Stacker male	Kabelfarbe cable colour
.1	schwarz black	L R N	schwarz black
.2	weiß white	L R N	weiß white
.3	grau grey	L R N	schwarz black
.5	rot red	L R N	schwarz black

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.232.XX04.F	XX in dm-Schritten	92.232.1004.1 = 10dm/L = 1000mm	GST18i3K1-S 15 10SW
U2.232.XX04.F	XX in m-Schritten	U2.232.1204.1 = 12 m/L=12000mm	GST18i3K1-S 15 X12SW

Typ/type: GST18i3K1-S 15 ..
 SW = schwarz/black
 WS = weiß/white
 GR01 = grau/grey
 RT03 = rot/red

Further data see catalog
further data see catalog